

MATERIAL SAFETY DATA SHEET

SUNBONNET Lemon Wax

Date Prepared: 12/18/2000 Date Revised: 12/18/2000

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name/Use: SUNBONNET Lemon Wax

MANUFACTURER

The Butcher Company 67 Forest Street Marlborough, MA 01752-3012

 Butcher Telephone Number:
 800-225-9475

 Emergency Telephone (24 hours):
 800-228-5635

 CHEMTREC (U.S./Can.):
 800-424-9300

 CHEMTREC (Int'I):
 +1 703-527-3887

2. COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT(S)	CAS NO.	% BY WEIGHT	
Mineral spirits	8030-30-6	10 - 25	
N-Butane	106-97-8	7 - 10	
Propane	74-98-6	1 – 3	

See Section 8 for Exposure Limits NA - Not Applicable

OSHA REGULATORY STATUS: This product is classified as hazardous under OSHA regulations.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Opaque, Off-White Aerosol. Lemon Odor. Causes Eye and Skin Irritation. Contents Under Pressure.

POTENTIAL HEALTH EFFECTS (See Section 11 for Toxicological Information)

PRIMARY ROUTE(s) OF EXPOSURE: X Eye X Skin Contact Skin Absorption X Inhalation X Ingestion

EFFECTS OF ACUTE EXPOSURE

EYES:

Causes eye irritation. Symptoms may include redness and pain.

SKIN:

Causes skin irritation. Symptoms may include redness, rash and mild swelling.

INHALATION:

High concentrations of vapor or mist may cause nose, throat and respiratory tract irritation. Symptoms may include coughing. High concentrations of vapor or mist may also cause central nervous system effects including headache, dizziness and nausea.

MSDS No: 4110 Page: 1 of 7

Date Prepared: 12/18/2000 Date Revised: 12/18/2000

INGESTION:

May cause mouth, throat and stomach irritation. Symptoms may include nausea, vomiting and diarrhea. May also cause central nervous system effects including headache, dizziness and weakness.

EFFECTS OF CHRONIC EXPOSURE:

Prolonged or repeated contact can cause defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

MEDICAL CONDITIONS AGGRAVATED:

May aggravate pre-existing eye, skin and respiratory conditions.

4. FIRST AID MEASURES

EYES:

Flush eyes with plenty of water while holding eyelids apart. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Do not put any medication in the victim's eyes unless instructed by a physician. Get medical attention.

SKIN:

Flush thoroughly with plenty of water, then wash with soap and water. Remove saturated clothing. Get medical attention if irritation develops or persists. Thoroughly wash (or discard) clothing and shoes before reuse.

INHALATION:

Remove to fresh air. If not breathing, give respiration; if breathing is difficult, give oxygen (by trained personnel only). Get medical attention if symptoms persist.

INGESTION:

Do not induce vomiting. Drink large quantities of water. Get immediate medical attention. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

FLASH POINT AND METHOD: Not applicable.

FLAMMABLE LIMITS:

Not applicable.

AUTOIGNITION TEMPERATURE: Not applicable.

EXTINGUISHING MEDIA:

Use water fog, dry chemical, CO2, or foam.

HAZARDOUS COMBUSTION PRODUCTS:

Normal products of combustion (carbon monoxide and carbon dioxide).

FIRE AND EXPLOSION HAZARDS:

Container is under pressure and may explode if exposed to excessive heat. Propellant retained by released material may be ignited by heat, sparks, flames, or other ignition sources.

MSDS No: 4110 Page: 2 of 7

Date Prepared: 12/18/2000 Date Revised: 12/18/2000

FIRE FIGHTING INSTRUCTIONS:

This product is not aerosol flammable per flame extension test 16 CFR 1500.45. If this product is involved in a fire, evacuate area. Cool containers exposed to fire with water. MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear should be worn.

6. ACCIDENTAL RELEASE MEASURES

See Section 8, Exposure Controls/Personal Protection and Section 3, Hazard Identification. Floors may be slippery. Use care to avoid falling. Remove ignition sources and ventilate spill area. Contain and isolate spill. Keep non-essential personnel from entering spill area. Use mop, absorbent and non-sparking tools to collect material for proper disposal. Rinse area with water.

7. HANDLING AND STORAGE

HANDLING:

Follow label use directions. Do not mix with other chemicals unless instructed by label directions. Avoid contact with skin, eyes and clothing. Use with adequate ventilation. Avoid breathing vapor or mist. Use spark-proof tools. Do not expose to heat. Do not use near sparks, flames or pilot lights. Do not puncture or incinerate container. Wash thoroughly after handling. Remove contaminated clothing. Wash clothing and equipment before reuse.

STORAGE:

Keep container closed when not in use. Store away from incompatible materials. (See Section 10, Stability and Reactivity). Store away from direct sunlight. Keep away from heat, sparks and flame. Do not store at temperatures above 120 F (49 C).

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT (PPE)

EYE:

Where eye contact is possible, wear safety glasses with side shields or chemical splash goggles (ANSI Z87.1 approved).

SKIN:

Where skin contact is possible, chemical-resistant clothing (e.g., gloves) should be worn.

RESPIRATORY:

No respiratory protection is required if ventilation is adequate.

ENGINEERING CONTROLS:

Good general room ventilation is expected to be adequate. If user operations generate vapor or mist, ventilation should be used to keep airborne concentrations below exposure limits.

MSDS No: 4110 Page: 3 of 7

Date Prepared: 12/18/2000 Date Revised: 12/18/2000

EXPOSURE LIMITS:

INGREDIENT(S) OSHA PEL/STEL ACGIH TLV/STEL

 Mineral spirits
 100 ppm (400 mg/m3)
 400 ppm (1590 mg/m3)

 N-Butane
 800 ppm (1900 mg/m3)
 800 ppm (1900 mg/m3)

 Propane
 1000 ppm (1800 mg/m3)
 2500 ppm (4508 mg/m3)

NA - Not Available

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Aerosol

ODOR: Lemon

APPEARANCE: Opaque, Off-White

pH: 8.8

PERCENT VOLATILE BY WEIGHT: Not Available VAPOR PRESSURE: 30-34 psig at 64°F at 18°C

VAPOR DENSITY: Not Available BOILING POINT: Not Available

FREEZING/MELTING POINT: Not Available SOLUBILITY IN WATER: Dispersible EVAPORATION RATE: Not Available SPECIFIC GRAVITY: Not Available

VISCOSITY: Water Thin

OCTANOL/WATER PARTITION COEFFICIENT: Not Available

ODOR THRESHOLD: Not Available

10. STABILITY AND REACTIVITY

STABILITY (CONDITIONS TO AVOID):

Stable.

POLYMERIZATION:

Will not occur.

HAZARDOUS DECOMPOSITION:

None known.

INCOMPATIBLE MATERIALS:

Oxidizers (e.g., bleach).

11. TOXICOLOGICAL INFORMATION

ACUTE DATA:

This product is a primary skin and eye irritant. Based on acute toxicity testing, it is not considered to be toxic by ingestion or inhalation. The following data are available for this product and its ingredients.

MSDS No: 4110 Page: 4 of 7

Date Prepared: 12/18/2000 Date Revised: 12/18/2000

PRODUCT/INGREDIENT	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
SUNBONNET Lemon Wax	>5000 mg/kg	Not Available	>44.88 mg/L (4-hr)
Mineral spirits	Not Available	Not Available	Not Available
N-Butane	Not Available	Not Available	658 g/m3 (4-hr)
Propane	Not Available	Not Available	Not Available

SENSITIZATION DATA:

No data available.

CHRONIC DATA:

Prolonged overexposure to aliphatic petroleum distillates by ingestion and inhalation has caused central nervous system effects in humans and laboratory animals; overexposure by inhalation has also caused kidney effects in animals.

REPRODUCTIVE/TERATOGENIC DATA:

No data available.

CARCINOGENIC/MUTAGENIC DATA:

Not listed as carcinogenic by NTP, IARC, or ACGIH or regulated as a carcinogen by OSHA.

SYNERGISTIC MATERIALS:

No data available.

12. ECOLOGICAL INFORMATION

No data available.

13. DISPOSAL CONSIDERATIONS

Disposal of this material should be in accordance with local, state or provincial and federal regulations. The unused product, as manufactured, is a RCRA non-hazardous waste in accordance with 40 CFR 261. The product has not been evaluated by the Toxicity Characteristic Leachate Procedure (TCLP). According to RCRA, it is the responsibility of the waste generator to ensure proper disposal.

14. TRANSPORT INFORMATION

DOT/TDG HAZARDOUS MATERIAL DESCRIPTION: Consumer Commodity DOT/TDG HAZARD CLASS: ORM-D

SPECIAL SHIPPING NOTES:

The ORM-D hazard class applies to U.S. transportation only.

15. REGULATORY INFORMATION

Not meant to be all-inclusive—selected regulations represented.

MSDS No: 4110 Page: 5 of 7

Date Prepared: 12/18/2000 Date Revised: 12/18/2000

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Under 40 CFR 370.2, this product meets the following hazard categories: Immediate, Delayed, Pressure Generating.

313 REPORTABLE INGREDIENTS: Ingredients in this product are not currently subject to notification.

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: None of the ingredients in this product are reportable under CERCLA.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: This product complies with all TSCA inventory requirements.

MASSACHUSETTS, NEW JERSEY, PENNSYLVANIA RIGHT-TO-KNOW:

INGREDIENT(S)	CAS NO.	STATE LISTING
Water	7732-18-5	Not Listed
Mineral spirits	8030-30-6	MA, NJ, PA
N-Butane	106-97-8	MA, NJ, PA
Propane	74-98-6	MA, NJ, PA


NA - Not Applicable

16. OTHER INFORMATION

HMIS RATING

HEALTH	-	2
FLAMMABILITY		3
REACTIVITY		0
PERSONAL PROTECTION		-

NFPA RATING



MSDS STATUS

Revision #: 1

This MSDS replaces the December 09, 1997 MSDS. Any changes in information are as follows:

Prepared By Date Prepared [] Print CHEMTREC Phone Number

In Section 9

Appearance (Group Field) for Vapor Pressure Density Odor Threshold (Group Field) for Boiling Point (Group Field) for Freezing Point (Group Field) for Specific Gravity (Group Field) for Evaporation Rate (Group Field) for Percent Volatile Coeff Oil/Water

MSDS No: 4110 Page: 6 of 7

Date Prepared: 12/18/2000 Date Revised: 12/18/2000

In Section 15 OSHA Hazard Comm. Rule

APPROVED BY: EH&S/Regulatory Affairs

APPROVAL DATE: 12/18/2000

The information on this data sheet represents our current data and best opinion as to the proper use in handling of the product under normal foreseeable conditions. Any use of this product which is not in conformance with this data sheet or product label, or which involves using the product in combination with any other product or any other process is the responsibility of the user.

MSDS No: 4110 Page: 7 of 7