Material Safety Data Sheet

5-29-2012



1. Chemical product and company identification

Product name

Castrol GTX 10W-40

MSDS#

452859

Code

452859-US07, US12, US13, CA01

Product use

Engine oils.

For specific application advice see appropriate Technical Data Sheet or consult our company

representative.

Manufacturer

BP Lubricants USA Inc. 1500 Valley Road Wayne, NJ 07470

Telephone: (973) 633-2200 Telecopier: (973) 633-7475

EMERGENCY HEALTH

INFORMATION:

1 (800) 447-8735

Outside the US: +1 703-527-3887 (CHEMTREC)

EMERGENCY SPILL

INFORMATION:

1 (800) 424-9300 CHEMTREC (USA)

OTHER PRODUCT 1 (866) 4 BP - MSDS

INFORMATION (866-427-6737 Toll Free - North America)

email: bpcares@bp.com

2. Composition/information on ingredients

ngredient name

%

Castrol GTX SAE 10w-40 Motor Oil

Base oil - highly refined Zinc alkyl dithiophosphate

Mixture 68649-42-3

CAS#

0 - 100 1 - 5

3. Hazards identification

Physical state

Liquid.

Color

Not available.

Emergency overview

CAUTION!

MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling. Prolonged or repeated contact can defeat the aking and lead to initiation, and the lead to initiation, and the lead to initiation.

defat the skin and lead to irritation, cracking and/or dermatitis.

Routes of entry

Dermal contact. Eye contact. Inhalation. Ingestion.

Potential health effects

Eyes

May cause eye irritation.

Skin

May cause skin irritation. Prolonged or repeated contact can defat the skin and lead to irritation

and/or dermatitis. Used engine oil may contain hazardous components which have the potential to

cause skin cancer.

Inhalation

May cause respiratory tract irritation.

Ingestion

Ingestion may cause gastrointestinal irritation and diarrhea.

Product Castrol GTX 10W-40

Product code

452859-US07, US12, US13, CA01

Page: 1/6

name

Version 1

Date of issue 05/29/2007.

Format US

Language ENGLISH.

Build 5.3.1

See toxicological Information (section 11).

I. First aid measures

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical

attention if irritation occurs.

Skin contact Immediately wash exposed skin with soap and water. Remove contaminated clothing and shoes.

Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention if

irritation develops.

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult,

give oxygen. Get medical attention.

Ingestion Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by

mouth to an unconscious person. Get medical attention if symptoms appear. If large quantities of

this material are swallowed, call a physician immediately.

5. Fire-fighting measures

Flammability of the

product

May be combustible at high temperature.

Flash point

>200 °C (Open cup)

Products of combustion

carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

nitrogen oxides (NO, NO₂ etc.) sulfur oxides (SO₂, SO₃ etc.)

phosphorus oxides metal oxide/oxides

Unusual fire/explosion

hazards

Non-explosive in the presence of the following materials or conditions: open flames, sparks and

static discharge, heat and shocks and mechanical impacts.

Tire-fighting media and instructions

In case of fire, use water fog, foam, dry chemicals, or carbon dioxide. Do not use water jet.

Protective clothing (fire)

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full

turnout gear.

6. Accidental release measures

Personal precautions

Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (See Section: "Exposure controls/personal protection"). Follow all fire fighting procedures (See Section: "Fire-fighting measures").

Environmental precautions and clean-up methods

If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal. Avoid contact of spilled material with soil and prevent runoff entering surface waterways. See Section 13 for Waste Disposal Information.

Personal protection in case of a large spill Chemical splash goggles. Chemical resistant protective suit. Boots. Chemical resistant gloves. Vapor respirator or a self-contained breathing apparatus. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

CAUTION: The protection provided by air-purifying respirators is limited. Use a positive pressure air-supplied respirator if there is any potential for an uncontrolled release, if exposure levels are not known, or if concentrations exceed the protection limits of air-purifying respirator.

Product Castrol GTX 10W-40 name

Product code

452859-US07, US12, US13, CA01

Page: 2/6

Version 1

Date of issue 05/29/2007.

Format US

Language ENGLISH.

Build 5.3.1

7. Handling and storage

Handling

Avoid contact with skin and clothing. Avoid prolonged or repeated contact with skin. Avoid contact with eyes. Use only with adequate ventilation Avoid breathing vapor or mist. Wash thoroughly after handling.

Storage

Keep container tightly closed. Keep container in a cool, well-ventilated area. Empty containers may contain harmful, flammable/combustible or explosive residue or vapors. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards.

8. Exposure controls/personal protection

Occupational exposure

limits

Ingredient name

Occupational exposure limits

Base oil - highly refined

ACGIH (United States).

STEL: 10 mg/m³ 15 minute(s). Form: Oil mist, mineral TWA: 5 mg/m³ 8 hour(s). Form: Oil mist, mineral

OSHA (United States).

TWA: 5 mg/m³ 8 hour(s). Form: Oil mist, mineral

Zinc alkyl dithiophosphate

None assigned.

Some states may enforce more stringent exposure limits.

Control Measures

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are close to the work-station location.

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating,

smoking and using the lavatory and at the end of the working period.

Personal protection

Eyes

Avoid contact with eyes. Chemical splash goggles.

Skin and body

Avoid contact with skin and clothing. In accordance with good industrial hygiene and safety work

practices, airborne exposures should be controlled to the lowest extent practicable.

Respiratory

Use only with adequate ventilation Avoid breathing vapor or mist.

Hands

Wear gloves that cannot be penetrated by chemicals or oil.

Recommended: Nitrile gloves.

The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Consult your supervisor or S.O.P. for special handling directions

Consult local authorities for acceptable exposure limits.

9. Physical and chemical properties

Physical state

Liquid.

Heat of combustion

Not available.

Pour Point

-36 to -33 °C

Specific gravity

0.863 to 0.872

Solubility

insoluble in water.

Viscosity

Kinematic: 13.71 to 14.5 mm²/s (13.71 to 14.5 cSt) at 100°C

Product Castrol GTX 10W-40

name

Product code

452859-US07, US12, US13, CA01 Page: 3/6

Version 1

Date of issue 05/29/2007.

Format US

Language ENGLISH.

Build 5.3.1

10. Stability and reactivity

Stability and reactivity

The product is stable.

Conditions to avoid

Not available.

Incompatibility with various substances

Reactive or incompatible with the following materials: oxidizing materials.

Hazardous decomposition

products

carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

nitrogen oxides (NO, NO₂ etc.) sulfur oxides (SO₂, SO₃ etc.)

phosphorus oxides metal oxide/oxides

Hazardous polymerization

Will not occur.

11. Toxicological information

Acute toxicity

USED ENGINE OILS

Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.

Chronic toxicity

Carcinogenic effects

No component of this product at levels greater than 0.1% is identified as a carcinogen by ACGIH or the International Agency for Research on Cancer (IARC). No component of this product present at levels greater than 0.1% is identified as a carcinogen by the U.S. National Toxicology Program (NTP) or the U.S. Occupational Safety and Health Act (OSHA).

Mutagenic effects

No component of this product at levels greater than 0.1% is classified by established regulatory

criteria as a mutagen.

Reproductive effects

No component of this product at levels greater than or equal to 0.1% is classified by established regulatory criteria as a reproductive toxin.

Teratogenic effects

No component of this product at levels greater than 0.1% is classified by established regulatory

criteria as teratogenic or embryotoxic.

12. Ecological information

Ecotoxicity

No testing has been performed by the manufacturer.

13. Disposal considerations

Waste information

Avoid contact of spilled material and runoff with soil and surface waterways. Consult an environmental professional to determine if local, regional or national regulations would classify spilled or contaminated materials as hazardous waste. Use only approved transporters, recyclers, treatment, storage or disposal facilities. Dispose of in accordance with all applicable local and national regulations.

Consult your local or regional authorities.

Product Castrol GTX 10W-40 name

Product code

452859-US07, US12, US13,

Page: 4/6

Version 1

Date of issue 05/29/2007.

Format US

Language ENGLISH.

Build 5.3.1

14. Transport information

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

15. Regulatory information

U.S. Federal regulations

United States inventory (TSCA 8b): All components are listed or exempted.

TSCA 12(b) one-time export notification:: Diphenylamine

TSCA 12(b) annual export notification: lead; Alkylated phenol (P-00-346)

This product is not regulated under Section 302 of SARA and 40 CFR Part 355.

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Castrol GTX

10W-40: Immediate (Acute) Health Hazard

SARA 313

Product name

CAS number

Concentration

Form R - Reporting requirements

Zinc alkyl dithiophosphate

68649-42-3

0 - 2.6666

Supplier notification

Zinc alkyl dithiophosphate

68649-42-3

0 - 2.6666

CERCLA Sections 102a/103 Hazardous Substances (40 CFR Part 302.4):: Zinc alkyl

dithiophosphate; Arsenic: 1 lbs. (0.4536 kg); Cadmium: 10 lbs. (4.536 kg); lead: 10 lbs. (4.536 kg);

Zinc alkyl dithiophosphate;

State regulations

Massachusetts Substances **Massachusetts RTK**: The following components are listed: MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED LIGHT PARAFFINIC

New Jersey Hazardous Substances New Jersey Hazardous Substances: The following components are listed: ZINC compounds

Pennsylvania RTK Hazardous Substances

Pennsylvania RTK: The following components are listed: ZINC COMPOUNDS

WARNING: This product contains a chemical known to the State of California to cause cancer. Paraffin oils, .; Arsenic

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Cadmium; lead

Inventories

Canada inventory: All components are listed or exempted.

Europe inventory: At least one component is not listed in EINECS but all such components are

listed in ELINCS.

Australia inventory (AICS): All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

Japan inventory (ENCS): At least one component is not listed.

Korea inventory (KECI): All components are listed or exempted.

Philippines inventory (PICCS): At least one component is not listed.

Product Castrol GTX 10W-40

name

Version 1

Date of issue 05/29/2007.

Product code

452859-US07, US12, US13,

Page: 5/6

Format US

Language ENGLISH.

Build 5.3.1

16. Other information

Label requirements

CAUTION!

MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION.

X

MAY CAUSE RESPIRATORY TRACT IRRITATION.

HMIS® Rating:

Health

National Fire

Flammability 1 Physical 0 Protection Association

Hazard Personal Association (U.S.A.)

protection

Fire hazard

Health To Instability

Specific hazard

History

Date of issue

05/29/2007.

Date of previous issue

No Previous Validation.

Prepared by

Product Stewardship

Notice to reader

NOTICE: This Material Safety Data Sheet is based upon data considered to be accurate at the time of its preparation. Despite our efforts, it may not be up to date or applicable to the circumstances of any particular case. We are not responsible for any damage or injury resulting from abnormal use, from any failure to follow appropriate practices or from hazards inherent in the nature of the product.

Product Castrol GTX 10W-40 name

Version 1

Date of issue 05/29/2007.

Product code

452859-US07, US12, US13, CA01

Page: 6/6

Format US

Language ENGLISH.

Build 5.3.1