

SAFETY DATA SHEET

1. Identification

Product identifier	1200 Color Shield Exterior 100% Acrylic Fl	at 100, 122, 222, 333, and 555
Other means of identification	None.	
Recommended use	Architectural Coating	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier	/Distributor information	
Company name	Kelly-Moore Paint Co., Inc.	
Address	987 Commercial St., San Carlos, CA 94070	
Telephone	1-800-874-4436	
E-mail	TAlvarez@kellymoore.com	
Contact person	Tiffany Alvarez Gonda	
Emergency phone number	CHEMTREC: 1-800-424-9300	
2. Hazard(s) identification		
Physical hazards	Not classified.	
Health hazards	Sensitization, skin	Category 1
	Carcinogenicity	Category 2
OSHA defined hazards	Not classified.	

Label elements



Signal word	Warning
Hazard statement	May cause an allergic skin reaction. Suspected of causing cancer.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist or vapor. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If on skin: Wash with plenty of water. If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	This product contains Diphenyl ketone at < 0.2% which is suspected of causing cancer (See Section 11).

3. Composition/information on ingredients

Chemical name	CAS number	%
Titanium dioxide	13463-67-7	< 16
Dichloro-2-n-octyl-4-isothiazoli n-3-one	64359-81-5	< 0.2
Diphenyl ketone	119-61-9	< 0.2

All concentrations are in percent by weight (kg) unless ingredient is a gas. Gas concentrations are in percent by volume (l).

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. Wear appropriate protective equipment and clothing during clean-up.
Methods and materials for containment and cleaning up	This product is moderately soluble in water. Should not be released into the environment. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Prevent product from entering drains. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Туре	Value	
Diphenyl ketone (CAS 119-61-9)	TWA	0.5 mg/m3	
Biological limit values	No biological exposure limits noted for	No biological exposure limits noted for the ingredient(s).	
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.		
Individual protection measures	s, such as personal protective equipm	nent	
Eye/face protection	Use safety glasses, goggles, or face shield to protect eyes.		
Skin protection Hand protection	Wear appropriate chemical resistant gloves.		
Skin protection			
Other	Wear appropriate chemical resistant	clothing. Use of an impervious apron is recommended.	
Respiratory protection	Chemical respirator with organic vapor cartridge and full facepiece.		
Thermal hazards	Wear appropriate thermal protective	clothing, when necessary.	
General hygiene considerations	allowed out of the workplace. Always	quirements. Contaminated work clothing should not be s observe good personal hygiene measures, such as washing e eating, drinking, and/or smoking. Routinely wash work remove contaminants.	

9. Physical and chemical properties

Appearance	Milky white to colored liquid.
Physical state	Liquid.
Form	Liquid.
Color	Various.
Odor	Slightly ammoniacal.
Odor threshold	Not available.
рН	7 - 10
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	Not available.
Evaporation rate	< 1 (n-BuAc=1)
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	> 1 (Air=1)
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Moderately soluble
Partition coefficient (n-octanol/water)	Not available.

Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
VOC	46.74 - 49.14 g/L

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Strong acids.
Hazardous decomposition products	Carbon oxides. Metal oxides.

11. Toxicological information

Information on likely routes of exposure

information on likely routes of e	zhoznie		
Inhalation	Prolonged inhalation may be harmful.		
Skin contact	May cause an allergic skin reaction.		
Eye contact	Direct contact with eyes may cause temporary irritation.		
Ingestion	Expected to be a low ingestion hazard.		
Symptoms related to the physical, chemical and toxicological characteristics	May cause an allergic skin reaction. Dermatitis. Rash.		
Information on toxicological effe	ects		
Acute toxicity	Ingestion may cause irritation and malaise. In high concentrations, vapors and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea.		
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.		
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.		
Respiratory or skin sensitizatior	1		
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	May cause an allergic skin reaction.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	The product contains a small amount of a substance that is suspected of causing cancer. Inhalation of titanium dioxide dust may cause cancer, however due to the physical form of the product, inhalation of dust is not likely.		
IARC Monographs. Overall I	Evaluation of Carcinogenicity		
Diphenyl ketone (CAS 11 Titanium dioxide (CAS 13 NTP Report on Carcinogens	463-67-7) 2	2B Possibly carcinogenic to humans. 2B Possibly carcinogenic to humans.	
Not listed. OSHA Specifically Regulate	d Substances (29 CFR 1910.100 [°]	1-1050)	
Not regulated.	-		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.		
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not an aspiration hazard.		
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.		
1200 Color Shield Exterior 100% Acry	ic Elat 100 122 222 333 and 555	S	DS

Components of the product may be absorbed into the body through the skin.

12. Ecological information

Further information

Ecotoxicity	Harmful to aquatic life with long lasting effects.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	This product is moderately water soluble and may disperse in soil.
Other adverse effects	None known.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according toNot established.Annex II of MARPOL 73/78 andthe IBC Code

15. Regulatory information

US federal regulations	This product is a "Haza Standard, 29 CFR 1910 All components are on	0.1200.	efined by the OSHA Hazard Communicat nventory List.	ion
TSCA Section 12(b) Export	Notification (40 CFR 707	7, Subpt. D)		
Diphenyl ketone (CAS 119-61-9) OSHA Specifically Regulated Substances (29 CFR 1			ime Export Notification only.	
Not regulated.				
CERCLA Hazardous Substa	ince List (40 CFR 302.4)			
Zinc oxide (CAS 1314-13-2)		LISTED		
Superfund Amendments and Reauthorization Act of 1986 (SARA)				
Hazard categories	Immediate Hazard - Ye Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No	S		
SARA 302 Extremely hazardous substance				
Not listed.				
SARA 311/312 Hazardous chemical	Yes			
SARA 313 (TRI reporting)				
Chemical name		CAS number	% by wt.	
Zinc oxide		1314-13-2	< 2	

Other federal regulations		
-	n 112 Hazardous Air Pollutants (HAPs) List	
Not regulated.	n 112(r) Accidental Release Prevention (40 CFR 68.130)	
Not regulated.		
Safe Drinking Water Act (SDWA)	Not regulated.	
US state regulations	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.	
1,4-Dioxane (CAS 1. Cadmium (CAS 744 Diphenyl ketone (CA Ethylbenzene (CAS Lead (CAS 7439-92- Methanol (CAS 67-5 Methyloxirane (CAS Oxirane (CAS 75-21 Quartz (CAS 14808- US. Massachusetts RTI Amorphous Silica: U Kaolin (CAS 1332-5 Silicon dioxide (CAS Talc (CAS 14807-96 Titanium dioxide (CA Zinc oxide (CAS 131 US. New Jersey Worket Amorphous Silica: U Kaolin (CAS 1332-5 Silicon dioxide (CAS Talc (CAS 14807-96 Titanium dioxide (CAS Talc (CAS 14807-96) Titanium dioxide (CAS Talc (CAS 14807-96) Titanium dioxide (CAS)	tion 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance 23-91-1) 0-43-9) IS 119-61-9) 100-41-4) -1) 6-1) 75-56-9) -8) 60-7) K - Substance List ncalcinated Diatomaceous Earth (CAS 61790-53-2) 8-7) 7631-86-9) -6) IS 13463-67-7) 4-13-2) r and Community Right-to-Know Act ncalcinated Diatomaceous Earth (CAS 61790-53-2) 8-7) -7631-86-9) -6) IS 13463-67-7) 4-13-2) r and Community Right-to-Know Law ncalcinated Diatomaceous Earth (CAS 61790-53-2) 8-7)	
Talc (CAS 14807-96 Titanium dioxide (CA Zinc oxide (CAS 131 US. Rhode Island RTK	-6) AS 13463-67-7)	
Aluminum hydroxide (CAS 21645-51-2) Amorphous Silica: Uncalcinated Diatomaceous Earth (CAS 61790-53-2) Kaolin (CAS 1332-58-7) Talc (CAS 14807-96-6) Titanium dioxide (CAS 13463-67-7)		
International Inventories		
Country(s) or regionInventory nameOn inventory (yes/notUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryYes*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).YesA "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).		
16. Other information, inc	luding date of preparation or last revision	
Issue date	16-December-2016	
Revision date	_	
Version #	01	
HMIS® ratings	Health: 2* Flammability: 1	

Kelly-Moore Paint Co., Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.