

MANGANOUS NITRATE, SOLUTION

MSDS Number: M0780 --- Effective Date: 12/08/96

1. Product Identification

Synonyms: Manganese nitrate solution; Manganese (II) nitrate solution; Manganese dinitrate solution CAS No.: Not applicable to mixtures. Molecular Weight: Not applicable to mixtures. Chemical Formula: Not applicable to mixtures. Product Codes: 2544, 2546

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
Nitric Acid, Manganese(2+) Salt	10377-66-9	50 - 72%	Yes
Nitric Acid	7697-37-2	5%	No
Water	7732-18-5	23 - 45%	No

3. Hazards Identification

Emergency Overview

POISON! DANGER! OXIDIZER. CONTACT WITH OTHER MATERIAL MAY CAUSE FIRE. CORROSIVE. LIQUID AND MIST CAUSE SEVERE BURNS TO ALL BODY TISSUE. MAY BE FATAL IF SWALLOWED. HARMFUL IF INHALED. AFFECTS LUNGS, CENTRAL NERVOUS SYSTEM, BLOOD AND KIDNEYS. INHALATION MAY CAUSE TOOTH DAMAGE.

J.T. Baker SAF-T-DATA^(tm) Ratings (Provided here for your convenience)

Health Rating: 2 - Moderate Flammability Rating: 0 - None Reactivity Rating: 3 - Severe (Oxidizer) Contact Rating: 3 - Severe (Corrosive) Lab Protective Equip: GOGGLES & SHIELD; LAB COAT & APRON; VENT HOOD; PROPER GLOVES Storage Color Code: Yellow (Reactive)

Potential Health Effects

Nitric acid is extremely hazardous; it is corrosive, reactive, an oxidizer, and a poison.

Inhalation:

Corrosive! Inhalation of vapors can cause breathing difficulties and lead to pneumonia and pulmonary edema, which may be fatal. Other symptoms may include coughing, choking, and irritation of the nose, throat, and respiratory tract. Inhalation can cause a flu-like illness (metal fume fever). This 24- to 48-hour illness is characterized by chills, fever, aching muscles, dryness in the mouth and throat and headache. Absorption of inorganic manganese salts through the lungs is poor but may occur in chronic poisoning.

Ingestion:

Corrosive! Swallowing nitric acid can cause immediate pain and burns of the mouth, throat, esophagus and gastrointestinal tract. May cause abdominal pain and nausea. Although they are poorly absorbed through the intestines, inorganic manganese salts may produce hypoglycemia and decreased calcium blood levels should absorption occur.

Skin Contact:

Corrosive! Can cause redness, pain, and severe skin burns. Concentrated solutions cause deep ulcers and stain skin a yellow or yellow-brown color.

Eye Contact:

Corrosive! Vapors are irritating and may cause damage to the eyes. Contact may cause severe burns and permanent eye damage.

Chronic Exposure:

Long-term exposure to concentrated vapors may cause erosion of teeth and lung damage. Long-term exposures seldom occur due to the corrosive properties of the acid. Chronic manganese poisoning can result from excessive inhalation and ingestion exposure and involves impairment of the central nervous system. Early symptoms include sluggishness, sleepiness, and weakness in the legs. Advanced cases have shown fixed facial expression, emotional disturbances, spastic gait, and falling. Illness closely resembles Parkinson's Disease. Kidney effects, blood changes and manganese psychosis also may occur as a result of chronic exposure. Chronic inhalation exposure can cause lung damage.

Aggravation of Pre-existing Conditions:

Persons with pre-existing skin disorders, eye disease, or cardiopulmonary diseases may be more susceptible to the effects of this substance. Persons with impaired respiratory function, psychiatric or neurological disturbances, and nutritional deficiencies may be more susceptible to the effect of this substance.

4. First Aid Measures

Immediate first aid treatment reduces the health effects of this substance.

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

Ingestion:

DO NOT INDUCE VOMITING! Give large quantities of water or milk if available. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Skin Contact:

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.

Eye Contact:

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Fire:

Not combustible, but substance is a strong oxidizer and its heat of reaction with reducing agents or combustibles may cause ignition. Can react with metals to release flammable hydrogen gas.

Explosion:

May react explosively with combustible organic or readily oxidizable materials such as: alcohols, turpentine, charcoal, organic refuse, metal powder, hydrogen sulfide, etc.

Fire Extinguishing Media:

If involved in a fire, use water spray.

Special Information:

Increases the flammability of combustible, organic and readily oxidizable materials. In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Keep combustibles (wood, paper, oil, etc.) away from spilled material. Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Neutralize with alkaline material (soda ash, lime), then absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect from physical damage and direct sunlight. Isolate from incompatible substances. Store above 16C (60F) to prevent freezing. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

For Nitric Acid: OSHA Permissible Exposure Limit (PEL): 2 ppm (TWA) ACGIH Threshold Limit Value (TLV): 2 ppm (TWA); 4 ppm (STEL) For Manganese Nitrate: - OSHA Permissible Exposure Limit (PEL): 5 mg/m3 Ceiling for manganese compounds as Mn - ACGIH Threshold Limit Value (TLV): 0.2 mg/m3 (TWA) for manganese, elemental and inorganic compounds as Mn

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded, wear a supplied air, full-facepiece respirator, airlined hood, or full-facepiece self-contained breathing apparatus. This material is an oxidizer and should not come in contact with cartridges and cannisters that contain oxidizable materials, such as activated charcoal. Canister-type respirators using sorbents are ineffective.

Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye Protection:

Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance: Pink solution.

Odor: Slight nitric acid odor.

Solubility: Infinitely soluble.

Specific Gravity: 1.54

pH: No information found.

% Volatiles by volume @ 21C (70F): No information found.

Boiling Point: 116C (241F)

Melting Point: No information found.

Vapor Density (Air=1): No information found.

Vapor Pressure (mm Hg): No information found.

Evaporation Rate (BuAc=1): No information found.

10. Stability and Reactivity

Stability:

Stable under ordinary conditions of use and storage. Containers may burst when heated.

Hazardous Decomposition Products:

When heated to decomposition, emits toxic nitrogen oxides fumes and hydrogen nitrate. Oxides of manganese may form when heated to decomposition.

Hazardous Polymerization:

Will not occur.

Incompatibilities:

A dangerously powerful oxidizing agent, concentrated nitric acid is incompatible with most substances, especially strong bases, metallic powders, carbides, hydrogen sulfide, turpentine, and combustible organics. Manganese nitrate is also an oxidizing agent that is incompatible with combustible organics.

Conditions to Avoid:

Heat, incompatibles.

11. Toxicological Information

For Manganese Nitrate: No LD50/LC50 information found relating to normal routes of occupational exposure. Investigated as a mutagen. For Nitric Acid: Investigated as a mutagen and reproductive effector.

\Cancer Lists\					
Trendint	NTP Carcinogen				
Ingreatent	Known	Anticipated			
Nitric Acid, Manganese(2+) Salt (10377-66-9)	No	No	None		
Nitric Acid (7697-37-2)	No	No	None		
Water (7732-18-5)	No	No	None		

12. Ecological Information

Environmental Fate: No information found.

Environmental Toxicity: No information found.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Domestic (Land, D.O.T.)

Proper Shipping Name: MANGANESE NITRATE, SOLUTION Hazard Class: 5.1 UN/NA: UN2724 Packing Group: III Information reported for product/size: 160LB

International (Water, I.M.O.)

Proper Shipping Name: MANGANESE NITRATE, SOLUTION Hazard Class: 5.1 UN/NA: UN2724 Packing Group: III Information reported for product/size: 160LB

International (Air, I.C.A.O.)

Proper Shipping Name: MANGANESE NITRATE, SOLUTION Hazard Class: 5.1 UN/NA: UN2724 Packing Group: III Information reported for product/size: 160LB

15. Regulatory Information

		TSCA	EC	Japan	Australia
lt (10377-	-66-9)	Yes	Yes	Yes	Yes
		Yes	Yes	Yes	Yes
		Yes	Yes	Yes	Yes
tatus - Pa	art 2\				
		Konos	C	anada וצחוע	Dhil
			·		
lt (10377-	-66-9)	Yes	Yes	No	Yes
		Yes	Yes	No	Yes
		Yes	Yes	No	Yes
ernational	l Regulati	Lons -	Part	1\	
	-SARA	4 302-		SAR	A 313
	RQ	TPQ	Li	st Che	emical Cate
lt	No	No	No	Man	nganese cm
	1000	1000	Ye	s	No
	No	No	No		No
ernational	l Regulati	ions -	Part	2\	
	CERCI			T 2 9	SCA-
	·				
lt	1		No	Ν	lo
	1000		No	Ν	lo
	No		No	Ν	lo
	No	No	No		

SARA 311/312: Acute: Yes Chronic: Yes Fire: Yes Pressure: No Reactivity: No (Mixture / Liquid)

Australian Hazchem Code: 1S Poison Schedule: S5

WHMIS:

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

16. Other Information

NFPA Ratings: Health: 3 Flammability: 0 Reactivity: 0 Other: Oxidizer

Label Hazard Warning:

POISON! DANGER! OXIDIZER. CONTACT WITH OTHER MATERIAL MAY CAUSE FIRE. CORROSIVE. LIQUID AND MIST CAUSE SEVERE BURNS TO ALL BODY TISSUE. MAY BE FATAL IF SWALLOWED. HARMFUL IF INHALED. AFFECTS LUNGS, CENTRAL NERVOUS SYSTEM, BLOOD AND KIDNEYS. INHALATION MAY CAUSE TOOTH DAMAGE.

Label Precautions:

Do not get in eyes, on skin, or on clothing. Do not breathe vapor or mist. Use only with adequate ventilation. Wash thoroughly after handling. Keep from contact with clothing and other combustible materials. Store in a tightly closed container.

Label First Aid:

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In all cases get medical attention immediately.

Product Use:

Laboratory Reagent.

Revision Information:

Mixture. New 16 section MSDS format, all sections have been revised.

Disclaimer:

Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. MALLINCKRODT BAKER, INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, MALLINCKRODT BAKER, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

Strategic Services Division Phone Number: (314) 539-1600 (U.S.A.)