

M A T E R I A L S A F E T Y D A T A S H E E T

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 6700

PRODUCT NAME: T-FLEX (A/10)

HMIS CODES: H C F R P

PRODUCT CODE: 6700

1 3 0 B

WHMIS CLASS: A & B,5 & D,2,B

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: ATCO International
ADDRESS : 1401 Barclay Circle,S.E.

Marietta, GA 30060

INFORMATION PHONE : (770)424-7550

DATE PRINTED: 01/12/2015

PREPARED BY: TECHNICAL SERVICES

REVISION DATE: 01/12/2015

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

Table with 5 columns: Reportable Components, CAS Number, PEL, TLV, and Weight Percent. Rows include Isoparaffinic Hydrocarbon, Liquified Petroleum Gas, and Ethanol.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: Approx. 133° F
SPECIFIC GRAVITY (H2O=1): 0.70
VAPOR DENSITY: ND
EVAPORATION RATE: ND
DENSITY: 6.00 lb/gl
MATERIAL V.O.C.: Approx. 60%
SOLUBILITY IN WATER: 5-15%
pH (Concentrate): NA
APPEARANCE: CLEAR LIQUID.
pH (Diluted): NA
ODOR: SOLVENT-LIKE.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

OSHA FLAMMABILITY CLASSIFICATION: EXTREMELY FLAMMABLE AEROSOL
FLASH POINT: 12° F (Conc. Only) METHOD USED: TOC
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: ND UPPER: ND

EXTINGUISHING MEDIA: Dry chemicals, Foam, or Carbon Dioxide.

SPECIAL FIREFIGHTING PROCEDURES: Keep containers cool with water spray. Avoid breathing decomposition products. Wear self-contained breathing apparatus and protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Exposure to temperatures above 120 deg.F may cause bursting.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 6700

===== SECTION V - REACTIVITY DATA =====

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: Open flame, sparks, or high temperature.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and or burning may produce oxides of carbon and various hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation X Eye Contact X
Skin Contact X Ingestion

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to upper respiratory tract, dizziness, nausea and other central nervous system effects.

EYE CONTACT: May cause stinging of eyes followed by irritation.

SKIN CONTACT: May cause skin irritation on repeated or prolonged contact.

SKIN ABSORPTION: No evidence of adverse effects from available information.

INGESTION: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of product into lungs can cause chemical pneumonia.

CHRONIC EFFECTS OF OVEREXPOSURE: There are no known chronic effects from this product.

CARCINOGENICITY: NTP CARCINOGEN: IARC MONOGRAPHS: OSHA REGULATED:

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: No additional effects of overexposure to this material can be found from available information.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid immediately.

EYE CONTACT: Immediately flush eyes with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

SKIN CONTACT: Wash exposed area thoroughly with soap and water. Consult a physician if irritation develops.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 6700

INGESTION: IF SWALLOWED: Call a physician immediately. Do NOT induce vomiting unless directed to do so by a physician. Never give anything by mouth to an unconscious person.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all ignition sources. Avoid breathing vapors. Shut off source of spill if it can be done safely. Use non-sparking tools. Absorb with inert, absorbant material and dispose of in accordance with applicable regulations.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in a dry, cool place away from heat or open flame. Do not store at temperatures above 120 F.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: None required in excess of normal ventilation.

VENTILATION: Local mechanical exhaust to provide normal ventilation.

PROTECTIVE GLOVES: Not required, but contact with skin must be avoided.

EYE PROTECTION: Safety eye protection to protect against splash of liquids and also aerosol size particles is recommended.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard X Reactivity Hazard

Acute Health Hazard X Chronic Health Hazard Pressure Hazard X

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: ORM-D Consumer Commodity

DOT HAZARD CLASS: Not Applicable

UN NUMBER: Not Applicable

DOT PACKING GROUP: Not Applicable

SPECIAL SHIPPING INFORMATION: Not Applicable

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.