



# Safety Data Sheet

Issue date 16-Dec-2014

Version 1

## 1. Identification of the Substance/Preparation and of the Company/Undertaking

### Product Identifier

**Product name** CHAMPION'S CHOICE SILICONE LUBRICANT  
**Chemical name** 7-7695-1

### Other means of identification

**Product code** FG 438-5351-2  
**Synonyms** Silicone Lubricant

### Recommended use of the chemical and restrictions on use

**Recommended Use** Multi-purpose lubricant with silicone.  
**Uses advised against** See directions for use on product's label.

### Details of the supplier of the safety data sheet

<b>Supplier Address</b>	<b>Manufacturer Address</b>
Chase Products Co.	Chase Products Co.
2727 Gardner Road	2727 Gardner Road
Broadview, IL 60155	Broadview, IL 60155
708-273-1121	708-273-1121

### Emergency Telephone Number

**Company Phone Number** 708-865-1000  
**24 Hour Emergency Phone Number** 1-800-255-3924  
**Emergency telephone** ChemTel 1-800-255-3924

## 2. Hazards Identification

### Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
FLAMMABLE AEROSOLS	Category 1
Gases Under Pressure	liquefied gas

### Label Elements

#### EMERGENCY OVERVIEW

**DANGER**

**hazard statements**  
 CAUSES SKIN IRRITATION  
 Causes serious eye irritation  
 May cause drowsiness or dizziness  
 May be fatal if swallowed and enters airways  
 EXTREMELY FLAMMABLE AEROSOL  
 Contains gas under pressure; may explode if heated



**Appearance** clear liquid

**Physical State** Aerosol

**Odor** Petroleum hydrocarbon odor.

**Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Wear protective gloves, protective clothing, eye protection and face protection.  
 Avoid breathing fumes, mist, vapors or spray.  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat, sparks, open flames and hot surfaces. — No smoking  
 Pressurized container: Do not pierce or burn, even after use  
 Do not spray on an open flame or other ignition source

**Precautionary Statements - Response**

Specific measures. See additional cautionary statements on this label.  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 IF ON SKIN: Wash with plenty of soap and water  
 If skin irritation occurs: Get medical advice/attention  
 Take off contaminated clothing and wash before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor if you feel unwell.  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor.  
 Do NOT induce vomiting

**Precautionary Statements - Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

**Other Information**

- Very toxic to aquatic life with long lasting effects
  - Very toxic to aquatic life
- 0% of the mixture consists of ingredient(s) of unknown toxicity

**3. Composition/information on Ingredients**

**Synonyms** Silicone Lubricant.  
**Chemical Family** MIXTURES.  
**Formula** 7-7695-1

Chemical name	CAS No	weight-%	Trade secret
Heptane	142-82-5	35-40	*
Acetone	67-64-1	35-40	*
Propane	74-98-6	10-15	*
n-butane	106-97-8	5-10	*

\* The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. First aid measures

### FIRST AID MEASURES

<b>Eye Contact</b>	Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
<b>Skin contact</b>	Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advise.
<b>inhalation</b>	If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an ambulance, then provide artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advise.
<b>INGESTION</b>	Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates. Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician immediately.

### Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness and nausea. Prolonged and repeated contact with skin may cause irritation and reddening. Contact with eyes causes irritation.
-----------------	--

### Indication of any immediate medical attention and special treatment needed

<b>Note to physicians</b>	Contains petroleum distillates, do not induce vomiting because of aspiration pneumonia hazard.
---------------------------	--

## 5. Fire-fighting measures

### Suitable extinguishing media

Dry chemical, CO2 or water spray.

**Unsuitable extinguishing media** Caution: Use of water spray when fighting fire may be inefficient.

### Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

**Hazardous combustion products** Thermal decomposition may release carbon monoxide and carbon dioxide.

### Explosion data

**Sensitivity to Mechanical Impact** Contents under pressure, keep away from heat and open flame.

**Sensitivity to Static Discharge** Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Use with adequate general or local exhaust ventilation.

**For emergency responders** Remove all sources of ignition.

### Environmental Precautions

**Environmental Precautions** See Section 12 for additional Ecological Information.

**Methods and material for containment and cleaning up**

**Methods for Containment** Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.

**Methods for cleaning up** Clean contaminated surface thoroughly.

**7. Handling and Storage**

**Precautions for safe handling**

**Advice on safe handling** Do not deliberately inhale vapor or spray mist. Avoid getting spray into eyes. Keep out of reach of children.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). **AEROSOL STORAGE LEVEL III (NFPA-30B).**

**Incompatible Materials** Avoid heat, open flame and contact with strong oxidizers.

**8. Exposure Controls/Personal Protection**

**Control parameters**

**Exposure guidelines** See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Heptane 142-82-5	STEL: 500 ppm TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m <sup>3</sup> (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m <sup>3</sup>	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 85 ppm TWA: 350 mg/m <sup>3</sup>
Acetone 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> (vacated) STEL: 2400 mg/m <sup>3</sup> The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup>	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>
n-butane 106-97-8	STEL: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>

**Appropriate engineering controls**

**Engineering controls** Use with adequate general or local exhaust ventilation.

**Individual protection measures, such as personal protective equipment**

**Eye/face Protection** Conventional eyeglasses to guard against splashing.

**Skin and Body Protection** Nitrile rubber gloves required.



**Conditions to Avoid**

Temperatures above 120 F.

**Incompatible Materials**

Avoid heat, open flame and contact with strong oxidizers.

**Hazardous decomposition products**

Thermal decomposition may yield gases like carbon monoxide and carbon dioxide.

**11. Toxicological Information**

**Information on likely routes of exposure**

<b>Product Information</b>	This product has not been tested as whole. See below for information on ingredients.
<b>inhalation</b>	no data available.
<b>Eye Contact</b>	no data available.
<b>Skin contact</b>	no data available.
<b>INGESTION</b>	no data available.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Heptane 142-82-5	-	= 3000 mg/kg ( Rabbit )	= 103 g/m <sup>3</sup> ( Rat ) 4 h
Acetone 67-64-1	= 5800 mg/kg ( Rat )	-	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
Propane 74-98-6	-	-	= 658 mg/L ( Rat ) 4 h
n-butane 106-97-8	-	-	= 658 g/m <sup>3</sup> ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

<b>Skin corrosion/irritation</b>	May cause skin irritation and reddening after prolonged or repeated contact with skin.
<b>Serious eye damage/eye irritation</b>	Irritating to eyes.
<b>irritation</b>	May cause skin and eye irritation.
<b>corrosivity</b>	Not applicable.
<b>sensitization</b>	No information available.
<b>Germ Cell Mutagenicity</b>	No information available.
<b>carcinogenicity</b>	Over exposure to petroleum solvents has been associated with nervous system damage.
<b>Reproductive Toxicity</b>	No information available.
<b>STOT - single exposure</b>	No information available.
<b>STOT - repeated exposure</b>	No information available.
<b>Aspiration Hazard</b>	No information available.

**Numerical measures of toxicity - Product Information**

<b>Unknown acute toxicity</b>	0% of the mixture consists of ingredient(s) of unknown toxicity
<b>The following values are calculated based on chapter 3.1 of the GHS document .</b>	
<b>ATEmix (oral)</b>	15483 mg/kg
<b>ATEmix (dermal)</b>	6821 mg/kg
<b>ATEmix (inhalation-gas)</b>	1397188 mg/l
<b>ATEmix (inhalation-dust/mist)</b>	143 mg/l
<b>ATEmix (inhalation-vapor)</b>	262 mg/l

**12. Ecological Information**

This product contains a chemical which, although not listed, meets the IMDG criteria for being a marine pollutant.

**ecotoxicity**

28.93% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Heptane 142-82-5		375.0: 96 h Cichlid fish mg/L LC50		10: 24 h Daphnia magna mg/L EC50
Acetone 67-64-1		6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 8300: 96 h Lepomis macrochirus mg/L LC50	EC50 = 14500 mg/L 15 min	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical name	Partition coefficient
Heptane 142-82-5	4.66
Acetone 67-64-1	-0.24
Propane 74-98-6	2.3
n-butane 106-97-8	2.89

**Other adverse effects**

No information available

**13. Disposal Considerations**

**Waste treatment methods**

**Disposal of wastes**

Dispose of in accordance with federal, state and local regulations.

**Contaminated packaging**

Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone 67-64-1		Included in waste stream: F039		U002

Chemical name	California Hazardous Waste Status
Heptane 142-82-5	Toxic Ignitable
Acetone 67-64-1	Ignitable

**14. Transport Information**

**DOT**

Limited quantity (LQ) Silicone Lubricant

**FG 438-5351-2 CHAMPION'S CHOICE SILICONE LUBRICANT**

<b>UN/ID no</b>	UN1950
<b>Proper Shipping Name</b>	Limited quantity (LQ)
<b>Hazard Class</b>	2.1
<b>Marine pollutant</b>	This product contains a chemical which, although not listed, meets the IMDG criteria for being a marine pollutant.

**15. Regulatory information**

**International Inventories**

**TSCA** All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

**DSL** All ingredients are listed or are excluded from listing on the DSL.

**Legend:**

*TSCA - United States Toxic Substances Control Act Section 8(b) Inventory*  
*DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List*

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

**SARA 311/312 Hazard Categories**

<b>Acute Health Hazard</b>	yes
<b>Chronic Health Hazard</b>	No
<b>Fire Hazard</b>	yes
<b>Sudden release of pressure hazard</b>	No
<b>Reactive Hazard</b>	No

**CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**US State Regulations**

**California Proposition 65**

This product does not contain any Proposition 65 chemicals

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania
Heptane 142-82-5	X	X	X
Acetone 67-64-1	X	X	X
Propane 74-98-6	X	X	X

**FG 438-5351-2 CHAMPION'S CHOICE SILICONE LUBRICANT**

n-butane 106-97-8	X	X	X
----------------------	---	---	---

**U.S. EPA Label information**

**EPA Pesticide registration number** Not applicable

**16. Other information**

<b>NFPA</b>	<b>Health Hazards</b> 2	<b>Flammability</b> 4	<b>Instability</b> 1	<b>Physical and chemical properties</b> Not applicable
<b>HMIS</b>	<b>Health Hazards</b> 2	<b>Flammability</b> 4	<b>Physical Hazards</b> 1	<b>Personal Protection</b> B

**Prepared by** Regulatory Department  
**Issue date** 16-Dec-2014

**Revision note**

This SDS supersedes a previous MSDS dated January 18, 2011.

**Disclaimer**

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**