

FRAZEE PAINT AND WALLCOVERING DIV OF REED HOLDINGS -- 216 700
EMC ELASTO-WALL -- 8010-00F056810

=====
Product Identification
=====

Product ID:216 700 EMC ELASTO-WALL
MSDS Date:09/19/1990
FSC:8010
NIIN:00F056810
Status Code:A
MSDS Number: CHZST
=== Responsible Party ===
Company Name:FRAZEE PAINT AND WALLCOVERING DIV OF REED HOLDINGS
Address:6625 MIRAMAR RD
City:SAN DIEGO
State:CA
ZIP:92121-2508
Country:US
Info Phone Num:619-276-9500
Emergency Phone Num:619-276-9500
Preparer's Name:ZEKE
CAGE:GO190
=== Contractor Identification ===
Company Name:FRAZEE INDUSTRIES INC
Address:6625 MIRAMAR RD
City:SAN DIEGO
State:CA
ZIP:92121
Country:US
Phone:858-626-3600
CAGE:1GK99
Company Name:FRAZEE PAINT AND WALLCOVERING
Address:6625 MIRAMAR RD
City:SAN DIEGO
State:CA
ZIP:92121-2508
Country:US
Phone:619-543-6000
CAGE:GO190

=====
Composition/Information on Ingredients
=====

Ingrid Name:VOLATILE ORGANIC CONTENT: 0.58 LB/GAL; 70 G/L COATING;
0.32 LB/GAL; 39 G/L MATERIAL.
RTECS #:9999999VO

Ingrid Name:ETHYLENE GLYCOL *98-2*
CAS:107-21-1
RTECS #:KW2975000
Fraction by Wt: 2%
Other REC Limits:10 MG/CUM
OSHA PEL:50 PPM
ACGIH TLV:C 127 MG/CUM
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: IRRITATION OF NOSE, THROAT
& LUNGS. INGESTION: HARMFUL, MAY CAUSE GASTROINTESTINAL IRRITATION.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, HEADACHE, NAUSEA, VOMITING,
DIARRHEA

=====
First Aid Measures
=====

First Aid:SKIN: CLEAN W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR.
EYES: FLUSH W/WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
Fire Fighting Measures
=====

Lower Limits:3.2
Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG
Fire Fighting Procedures:FOLLOW RECOMMENDED PROCEDURES IN HANDLING FIRE
AREAS. WEAR ADEQUATE FIRE FIGHTING EQUIPMENT W/A SELF CONTAINED
BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:POLYMER FILM CAN BURN, MATERIAL CAN
SPLATTER >212F.

=====
Accidental Release Measures
=====

Spill Release Procedures:WIPE UP IMMEDIATELY & SAFELY DISCARD
ABSORBENTS. LARGE: DIKE THE AREA & PUMP THE MATERIAL TO AN SPA
PERMITTED WASTE TANK.

=====
Handling and Storage
=====

Handling and Storage Precautions:USE W/ADEQUATE VENTILATION. KEEP AWAY
FROM EXCESSIVE HEAT.
Other Precautions:AVOID PROLONGED BREATHING OF VAPOR. AVOID
PROLONGED/REPEATED SKIN CONTACT.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:WHEN SPRAYING THIS MATERIAL, USE A NIOSH
APPROVED CARTRIDGE RESPIRATOR/GAS MASK TO KEEP AIRBORNE MISTS &
VAPOR CONCENTRATIONS <1
Spec Gravity:1.4
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:DILUTABLE
Appearance and Odor:WHITE VISCOUS LIQUID W/MILD ODOR

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
WATER REACTIVE, STRONG ALKALINE, ACIDIC SUBSTANCES
Stability Condition to Avoid:TEMPS >212F, EXCESS HEAT, TEMPS <40F,
FREEZING
Hazardous Decomposition Products:CO, CO2 ON COMBUSTION

=====
Disposal Considerations
=====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE &
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.