## FRAZEE PAINT AND WALLCOVERING -- 520E415 W/B SEMI GLOSS LAC -- 8010-00F026449

Product ID:520E415 W/B SEMI GLOSS LAC MSDS Date:05/31/1991 FSC:8010 NIIN:00F026449 MSDS Number: BQJGK === Responsible Party === Company Name: FRAZEE PAINT AND WALLCOVERING Address:6625 MIRAMAR RD City:SAN DIEGO State:CA ZIP:92121-2508 Country:US Info Phone Num: 619-276-9500 Emergency Phone Num: 619-276-9500 Preparer's Name:ZEKE CAGE:6D488 === Contractor Identification === Company Name: FRAZEE S R CO (FRAZEE INDUSTRIES) Address:6625 MIRAMAR RD City:SAN DIEGO State:CA ZIP:92121-2508 Country:US Phone: 619-276-9500/619-543-6000 CAGE:6D488 Ingred Name: SOLVENT NAPHTHA, PETROLEUM, LIGHT AROMATIC, HIGH FLASH AROMATIC NAPHTHA CAS:64742-95-6 RTECS #:WF3400000 Fraction by Wt: <5.0% Ingred Name: 2-BUTOXYETHANOL (ETHYLENEGLYCOL MONOBUTYL ETHER), BUTYL CELLOSOLVE, BUTYL GLYCOL, GLYCOL ETHER EB CAS:111-76-2 RTECS #:KJ8575000 Fraction by Wt: 1% Other REC Limits: 25 PPM (SKIN) OSHA PEL:S, 50 PPM ACGIH TLV:S, 25 PPM; 9293 Ingred Name: DIETHYLENE GLYCOL ETHYL ETHER, CARBITOL, CARBITOL CELLOSOLVEETHOXY DIGLYCOL, 2-(2-ETHOXYETHOXY)-ETHANOL CAS:111-90-0 RTECS #:KK8750000 Fraction by Wt: 2% Ingred Name: PROPYLENE GLYCOL METHYL ETHER (1-METHOXY-2-PROPANOL) PROPYLENE GLYCOL MONO METHYL ETHER CAS:107-98-2 RTECS #:UB7700000 Fraction by Wt: 4% Other REC Limits:100 PPM ACGIH TLV:100 PPM Ingred Name: VOL ORGANIC CMPD: COATING = 2.47 LB/GL (296 G/L); MATERIAL = 0.95 LB/GL (114 G/L)RTECS #:9999999VO

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: INHALATION: VAPOR OR MIST CAN CAUSE HEADACHE, NAUSEA, & IRRITATION OF THE NOSE, THROAT & LUNGS. SKIN/EYES: IRRITATION. INGESTION: HARMFUL. NAUSEA, VOMITING, DIARRHEA & GASTROINTESTINAL IRRITATION. Explanation of Carcinogenicity:NONE First Aid:SKIN: WASH W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH W/WATER FOR AT LEAST 15 MINS. INGESTION: OBTAIN MEDICAL ATTENTION IN ALL CASES. Lower Limits:1.0% Upper Limits:12.0% Extinguishing Media: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG Fire Fighting Procedures:WEAR ADEQUATE FIRE FIGHTING EQUIPMENT INCLUDING A SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard: POLYMER FILM CAN BURN. MATERIAL CAN SPLATTER ABOVE 212F. EXCESS HEAT MAY CAUSE CONTAINERS TO RUPTURE. Spill Release Procedures: WIPE UP IMMEDIATELY & SAFELY DISCARD ABSORBENTS. IN THE EVENT OF LARGE SPILLS, DIKE THE AREA & PUMP THE MATERIAL TO AN EPA PERMITTED WASTE TANK. Handling and Storage Precautions: USE ADEQUATE VENTILATION. KEEP AWAY FROM EXCESSIVE HEAT. Other Precautions: AVOID PROLONGED BREATHING OF VAPOR. AVOID SKIN & EYE CONTACT. Respiratory Protection: USE A NIOSH APPROVED CARTRIDGE RESPIRATOR OR GAS MASK WHEN SPRAYING. IN POORLY VENTILATED & CONFINED SPACES USE A FRESH-AIR SUPPLYING RESPIRATOR OR SELF-CONTAINED BREATHING APPARATUS Ventilation: GOOD VENTILATION TO KEEP BELOW TLV VALUES. Protective Gloves:RECOMMENDED Eye Protection: GOGGLES OR FACE SHIELD Other Protective Equipment: IMPERVIOUS CLOTHING, BOOTS, EYE WASHES, SAFETY SHOWERS. Work Hygienic Practices: REMOVE & WASH CONTAMINATED CLOTHES BEFORE REUSE. USE BARRIER CREAMS, SHOWERS & CHANGE CLOTHES. WASH HANDS THOROUGHLY. Supplemental Safety and Health Boiling Pt:B.P. Text:212F WATER Vapor Density:<1 Spec Gravity:1.0 Evaporation Rate & Reference: SLOWER THAN ETHER Appearance and Odor: TURBID VISCOUS LIQUID. MILD ODOR. 

Stability Indicator/Materials to Avoid:YES
THAT ARE WATER REACTIVE. STRONG ALKALINE & ACIDIC SUBSTANCES.
Stability Condition to Avoid:AVOID TEMPERATURES <40F, FREEZING
CONDITIONS & ALL SOURCES OF HEAT.
Hazardous Decomposition Products:CO, CO2, ON COMBUSTION</pre>

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.