

FRAZEE PAINT AND WALLCOVERING DIV OF REED HOLDINGS -- 216 700 EMC ELASTO-WALL -- 8010-00F056810

=====  
Product Identification  
=====

Product ID:216 700 EMC ELASTO-WALL  
MSDS Date:09/19/1990  
FSC:8010  
NIIN:00F056810  
Status Code:A  
MSDS Number: CHZST  
=== Responsible Party ===  
Company Name:FRAZEE PAINT AND WALLCOVERING DIV OF REED HOLDINGS  
Address:6625 MIRAMAR RD  
City:SAN DIEGO  
State:CA  
ZIP:92121-2508  
Country:US  
Info Phone Num:619-276-9500  
Emergency Phone Num:619-276-9500  
Preparer's Name:ZEKE  
CAGE:G0190

==== Contractor Identification ===  
Company Name:FRAZEE INDUSTRIES INC  
Address:6625 MIRAMAR RD  
City:SAN DIEGO  
State:CA  
ZIP:92121  
Country:US  
Phone:858-626-3600  
CAGE:1GK99  
Company Name:FRAZEE PAINT AND WALLCOVERING  
Address:6625 MIRAMAR RD  
City:SAN DIEGO  
State:CA  
ZIP:92121-2508  
Country:US  
Phone:619-543-6000  
CAGE:G0190

=====  
Composition/Information on Ingredients  
=====

Ingred Name:VOLATILE ORGANIC CONTENT: 0.58 LB/GAL; 70 G/L COATING;  
0.32 LB/GAL; 39 G/L MATERIAL.  
RTECS #:9999999VO

Ingred Name:ETHYLENE GLYCOL \*98-2\*  
CAS:107-21-1  
RTECS #:KW2975000  
Fraction by Wt: 2%  
Other REC Limits:10 MG/CUM  
OSHA PEL:50 PPM  
ACGIH TLV:C 127 MG/CUM  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION: IRRITATION OF NOSE, THROAT  
& LUNGS. INGESTION: HARMFUL, MAY CAUSE GASTROINTESTINAL IRRITATION.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:IRRITATION, HEADACHE, NAUSEA, VOMITING,

DIARRHEA

=====  
First Aid Measures  
=====

First Aid:SKIN: CLEAN W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR.  
EYES: FLUSH W/WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====  
Fire Fighting Measures  
=====

Lower Limits:3.2  
Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG  
Fire Fighting Procedures:FOLLOW RECOMMENDED PROCEDURES IN HANDLING FIRE  
AREAS. WEAR ADEQUATE FIRE FIGHTING EQUIPMENT W/A SELF CONTAINED  
BREATHING APPARATUS.  
Unusual Fire/Explosion Hazard:POLYMER FILM CAN BURN, MATERIAL CAN  
SPLATTER >212F.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:WIPE UP IMMEDIATELY & SAFELY DISCARD  
ABSORBENTS. LARGE: DIKE THE AREA & PUMP THE MATERIAL TO AN SPA  
PERMITTED WASTE TANK.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:USE W/ADEQUATE VENTILATION. KEEP AWAY  
FROM EXCESSIVE HEAT.  
Other Precautions:AVOID PROLONGED BREATHING OF VAPOR. AVOID  
PROLONGED/REPEATED SKIN CONTACT.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:WHEN SPRAYING THIS MATERIAL, USE A NIOSH  
APPROVED CARTRIDGE RESPIRATOR/GAS MASK TO KEEP AIRBORNE MISTS &  
VAPOR CONCENTRATIONS <1  
Spec Gravity:1.4  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Solubility in Water:DILUTABLE  
Appearance and Odor:WHITE VISCOUS LIQUID W/MILD ODOR

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES  
WATER REACTIVE, STRONG ALKALINE, ACIDIC SUBSTANCES  
Stability Condition to Avoid:TEMPS >212F, EXCESS HEAT, TEMPS <40F,  
FREEZING  
Hazardous Decomposition Products:CO, CO2 ON COMBUSTION

=====  
Disposal Considerations  
=====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE &  
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.