
67952 ELECTRIC CONTACT CLEANER

MSDS Number

BCPNS

National Stock Number

6850-00N008161

Product Name

67952 ELECTRIC CONTACT CLEANER

Manufacturer

KAR PRODUCTS INC DISTRIBUTOR

Product Identification

Product ID:67952 ELECTRIC CONTACT CLEANER
MSDS Date:03/17/1989
FSC:6850
NIIN:00N008161
MSDS Number: BCPNS

Responsible Party

KAR PRODUCTS INC./DISTRIBUTOR
461 NORTH THIRD AVENUE
DES PLAINES , IL 60016
US

Emergency Phone: 312-296-6111

Info Phone: 312-296-6111

Cage: 5L381

Contractor

KAR PRODUCTS
DES PLAINES, IL 60016
US

847-296-6111

Cage: 5L381

Ingredients

PERCHLOROETHYLENE (TETRACHLOROETHYLENE) (SARA III)

CAS: 127-18-4

RTECS: KX3850000

Fraction By Weight: 25%

OSHA PEL100 PPM

ACGIH TLV: 25PPM/100,A3 STEL;94

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS: 71-55-6

RTECS: KJ2975000

Fraction By Weight: 75%

OSHA PEL350 PPM/450 STEL
ACGIH TLV: 350 PPM/450STEL;9192
EPA Report Quantity: 1000 LBS
DOT Report Quantity: 1000 LBS

PROPANE
CAS: 74-98-6
RTECS: TX2275000
OSHA PEL1000 PPM
ACGIH TLV: ASPHYXIAN; 9192

Hazards

Effects of Overexposure:MAY CAUSE DIZZINESS OR,IN EXTREME CASES,ABSENCE OF O*2 COULD PRODUCE NARCOSIS.

First Aid

First Aid:EYES:FLUSH IMMEDIATELY WITH LARGE QUANTITIES OF H*2O FOR @ LEAST 15 MIN. INHAL:IF UNCONSCIOUS,REMOVE PERSON TO FRESH AIR & CALL PHYSICIAN.

Fire Fighting

Extinguishing Media:USE WATER FOG, DRY CHEMICAL OR CARBON DIOXIDE.
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED PRESSURE DEMAND SCBA & FULL PROTECTIVE EQUIPMENT .
Unusual Fire/Explosion Hazard:THERMAL DECOMPOSITION PRODUCTS MAY INCLUDE HCL & PHOSGENE . HEATED CAN MAY RUPTURE, VENT OR BURST.

Accidental Release

Spill Release Procedures:FLUSH WITH LARGE QUANTITIES OF H*2O & VENTIALTE AREA.

Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.READ & FOLLOW CAUTIONS ON PROD LABEL.PRACTICE GOOD HABITS OF CLEANLINESS.
Other Precautions:NO SMOKING IN AREA OF USE.DONT USE IN GENL VICINITY OF ARC WELDING,OPEN FLAMES/HOT SURFACES.HEAT &OR UV RADIATION MAY CAUSE HCL &/OR PHOSGENE FORMATION.

Exposure Controls

Respiratory Protection:NIOSH/MSHA APPROVED RESP PROT DEPENDING ON CONDITION OF USE.
Ventilation:NORMAL LOCAL EXHAUS VENTILATION.
Protective Gloves:RUBBER/PLASTIC
Eye Protection:SAFETY GLASSES
Other Protective Equipment:NOT REQUIRED (MFR)
Supplemental Safety and Health
VAP PRESS:< 140 @ 130F. SPECIAL FIRE FIGHT PROC:CNTNR COOL.USE EQUIP/SHIELDING TO PROTECT AGAINST BURSTING/VENTING CNTNRS. DATE OF PREP:7-23-86.

Chemical Properties

Boiling Pt:B.P. Text:>162F,>72C
Vapor Pres:100
Vapor Density:4
Spec Gravity:1.3 (H*2O=1)
Evaporation Rate & Reference:3.5 (BUTYL ACETATE=1)
Solubility in Water:NIL
Appearance and Odor:CLEAR; ETHEREAL ODOR.

Stability

Stability Indicator/Materials to Avoid: YES
INCOMPATIBLE W/STRONG OXIDIZER & ACTIVE METALS.
Stability Condition to Avoid: HIGH TEMPERATURES, SPARKS OR OPEN FLAME.
Hazardous Decomposition Products: FROM
BURNING-CO*2, CO, H*2O, HCL, PHOSGENE.

Disposal

Waste Disposal Methods: DO NOT PUNCTURE/INCINERATE CONTAINERS. GIVE TO A DISPOSAL SERVICE EQUIPPED TO SAFELY HANDLE & DISPOSE OF PRESSURIZED CONTAINERS IAW LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.