ANTI-STATIC SPRAY

HMIS RATING

Health	1
Flammability	3
Reactivity	0

FLASH POINT...

MATERIAL SAFETY DATA SHEET

NFPA 704 RATING
Health 1
Flammability 4
Reactivity 0
NFPA 30B LEVEL
N/A

KIMBALL-MIDWEST P.O. BOX 2470 COLUMBUS, OH 43216-2470

CORPORATE & EMERGENCY TELEPHONE: 800-424-9300

1. PRODUCT IDENTIFICATION

PART NUMBER	
PRODUCT NAME CHEMICAL FAMILY	
DOT SHIPPING	

2. HAZARDOUS INGREDIENTS

OSHA PEL	REL	ACGIH TLV	%
1000ppm	-	1000ppm	70-80
-	-	1000ppm	15-20
1000ppm	-	1000ppm	5-8
Non-hazardous and other components below reportable levels		0.1-1	
	1000ppm - 1000ppm	1000ppm 1000ppm -	1000ppm - 1000ppm 1000ppm 1000ppm - 1000ppm

All chemical compounds marked with an asterisk (*) are toxic chemicals subject to the reporting of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372. You must notify each person to whom this mixture of trade name product is sold. This statement must not be detached. Any copy or redistribution of this Material Safety Data Sheet shall include this statement. **Ceiling

3 PHYSICAL DATA

BOILING POINT (RANGE)	127.4 F
VAPOR PRESSURE PSIG @ 70°F	43-53
VAPOR DENSITY (AIR = 1)	>1
SOLUBILITY IN WATER	Negligible
SPECIFIC GRAVITY (H2O = 1)	0.7163
MELTING/FREEZING POINT	N/A
EVAPORATION RATE (61%=1)	<1
VOC content (by weight)	N/A
APPEARANCE AND ODOR	Clear, colorless compressed
	liquefied gas / characteristic
	odor

4. FIRE AND EXPLOSION DATA

UPPER EXPLOSIVE LIMIT (%)	.9.2%
LOWER EXPLOSIVE LIMIT (%)	. 1.8%
EXTINGUISHING MEDIA	.Carbon Dioxide, foam and/or dry chemical.
SPECIAL FIREFIGHTING PROCEDURES	Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.
FIRE AND EXPLOSION HAZARDS	.Fire may produce irritating,

5. HEALTH FFFFCTS DATA

corrosive and/or toxic gases.

SHORT TERM EFFECTS OF EXPOSURE	
ROUTE OF ENTRY	Skin absorption, Inhalation, Ingestion, Eye contact, Skin contact
HEALTH HAZARDS	Contact
(ACUTE AND CHRONIC)	Irritating to eyes. Can cause adverse reproductive effects. Prolonged exposure may cause chronic effects: unconsciousness. Sterility, Liver injury may occur. May cause CNS disorder and/or damage. May cause delayed lung damage. Pregnant women or women of child-bearing age should not be exposed to this product. Signs and symptoms include discomfort in the chest. Narcosis. Cyanosis. Liver enlargement. Jaundice. Defatting of the skin. Irritation. Birth defects. Sterility.
EYE CONTACT	Causes eye irritation.
SKIN CONTACT	Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis.
INHALATION	Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful.
INGESTION	Exposure by ingestion of an aerosol is unlikely. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause delayed lung damage.

5 HEALTH FEFECTS DATA (CONT'D)

	FIRST AID PROCEDURES
EYE CONTACT	Immediately flush eyes with plenty of waterfor at least 15 minutes. Remove contact lenses. Get medical attention
	if irritation develops or persists.
	Immediately remove contaminated clothing. Wash with warm water and soap. Get medical attention if irritation develops or persists.
	Have victim rinse mouth thoroughly with water. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim has ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.
INHALATION	Move to fresh air. Get medical attention if symptoms develop or persist.

SPECIAL HEALTH EFFECTS

CARCINOGEN (OSHA Guidelines).......This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

6 REACTIVITY

Risk of ignition. Stable under
normal conditions.
Isocyanates. Heat, flames and
sparks.
May include oxides of nitrogen.
Will not occur under normal
conditions.
None known.

7. PRECAUTIONS FOR SAFE HANDLING & USE

PROTECTIVE EQUIPMENT	
REQUIREMENTS	Safety goggles. Local exhaust ventilation may be necessary to control air contaminants to within TLVs during the use of this product.
WASH REQUIREMENTS	Wash with soap and water.
SPILL OR LEAK PROCEDURES	Absorb spill with inert material (e.g. dry sand or earth), then place in chemical waste container.
WASTE DISPOSAL METHODS	Dispose of in accordance with local, state, and federal regulations.
HANDLING & STORAGE	Wash thoroughly after handling. Keep away from heat, sparks, and flames. Store below 120°F.
OTHER PRECAUTIONS	Use NIOSH approved respirator with an organic vapor cartridge; avoid prolonged breathing of vapors; protection provided by air purifying respirators is limited.

8. ADDITIONAL INFORMATION

Use self-contained breathing apparatus if TLV limits are exceeded. Do not eat or smoke while using. Wash hands after use. Use positive pressure air supplied respirator if there is potential for uncontrolled release, if exposure levels are unknown, or in any circumstance where air purifying respirators may not provide adequate protection.

THE INFORMATION GIVEN AND THE RECOMMENDATIONS MADE HEREIN APPLY TO OUR PRODUCT(S) ALONE AND ARE NOT COMBINED WITH OTHER PRODUCTS. SUCH INFORMATIONIS BASED UPON OUR RESEARCH AND ON DATA FROM OTHER RELIABLE SOURCES AND IS BELIEVED TO BE ACCURATE. NO GUARANTEE OF ACCURACY IS MADE. IT IS THE PURCHASER'S RESPONSIBILITY BEFORE USING ANY PRODUCT TO VERIFYTHIS DATA UNDERTHEIR OWN OPERATING CONDITIONS AND TO DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PURPOSES.



Specializing in Materials Management since 1923