

## - MATERIAL SAFETY DATA SHEET -

COMPLIES WITH USOL SAFETY AND HEALTH REGULATIONS, (29 CFR 1910.1200)

EMERGENCY PHONE: (704) 875-6513

MSDS REFERENCE: 20810

REVISION DATE: 12/9/85

## SECTION 1 - IDENTIFICATION

MANUFACTURED FOR: MAINTENANCE SUPPLY CO., INC.  
P.O. BOX 493  
HUNTERSVILLE, NC 28078

PRODUCT: GRAFFITI REMOVER

TRADE NAME: VANISH 106

## SECTION 2 - HAZARDOUS INGREDIENTS

COMPOSITION	%	PEL/TLV
METHYL BENZENE (CAS # 108-98-3)	> 45	100 PPM
2-PROPANOL (CAS # 67-63-0)	< 20	400 PPM
2-BUTANONE (CAS # 78-93-3)	< 10	200 PPM
1,1,1-TRICHLOROETHANE (CAS # 71-55-6)	< 10	350 PPM
1,2-ETHANEDIOL (CAS # 107-21-1) -CEILING-	< 10	50 PPM
PROPELLANT: CARBON DIOXIDE (CAS # 124-38-9)	< 5	5000 PPM

## SECTION 3 - PHYSICAL DATA (ON CONCENTRATE)

BOILING POINT: IBP 165 DEGREES F.  
VAPOR PRESSURE (MM HG): 41 @ 20 DEGREES C.  
VAPOR DENSITY (AIR=1): 2.9  
SOLUBILITY IN WATER: NEGLIGIBLE  
SPECIFIC GRAVITY, (H2O=1): 0.893  
PERCENT VOLATILE BY VOLUME: OVER 95  
EVAPORATION RATE, (B. ACET.): 2.3  
APPEARANCE AND ODOR: CLEAR, THIN LIQUID HAVING AN AROMATIC ODOR

## SECTION 4 - FIRE AND EXPLOSION HAZARDS

FLASH POINT: 37 DEGREES F. - METHOD, T.C.C.  
FLAMMABLE LIMITS: LEL-2, UEL-12  
EXTINGUISHING MEDIA: CO2, FOAM OR DRY CHEMICAL  
SPECIAL FIRE FIGHTING PROCEDURE: KEEP CONTAINERS COOL. USE SHIELDING TO PROTECT PERSONNEL AGAINST BURSTING, RUPTURING OR VENTING CONTAINERS.  
UNUSUAL FIRE AND EXPLOSION HAZARDS: AT ELEVATED TEMPERATURES (OVER 130 DEGREES F.) CONTAINERS MAY VENT, RUPTURE OR BURST