



## Material Safety Data Sheet

---

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### Product Identification

**Product ID:** 140.0003457  
**Product Name:** AUST TMBR OIL AMBERWOOD  
**Product Use:** Paint product.  
**Print date:** 12/Jul/2012  
**Revision Date:** 06/Dec/2011

#### Company Identification

The Valspar Corporation - Architectural Coatings Division  
1191 Wheeling Road  
Wheeling, IL 60090

**Manufacturer's Phone:** 1-847-520-8580

**24-Hour Medical Emergency Phone:** 1-888-345-5732

### 2. HAZARDS IDENTIFICATION

#### Primary Routes of Exposure:

Inhalation  
Ingestion  
Skin absorption

#### Eye Contact:

- Moderate eye irritation

#### Skin Contact:

- Causes skin irritation.
- May cause defatting of the skin.
- Dermatitis
- Harmful if absorbed through skin.
- May cause sensitization by skin contact.
- Can be absorbed through skin.

#### Ingestion:

- Irritation of the mouth, throat, and stomach.
- Aspiration hazard if swallowed - can enter lungs and cause damage.

#### **Inhalation:**

- Causes respiratory tract irritation.
- Harmful by inhalation.
- May cause bronchopneumonia or bronchitis.

#### **Target Organ and Other Health Effects:**

- Kidney injury may occur.
- Liver injury may occur.
- Causes headache, drowsiness or other effects to the central nervous system.
- Blood disorders

#### **This product contains ingredients that may contribute to the following potential chronic health effects:**

- Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- Possible sensitization.

### **3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS**

| <b>Ingredient Name<br/>CAS-No.</b> | <b>Approx.<br/>Weight %</b> | <b>Chemical Name</b>                      |
|------------------------------------|-----------------------------|-------------------------------------------|
| STODDARD SOLVENT<br>8052-41-3      | 35 - 40                     | Stoddard solvent                          |
| MINERAL SPIRITS<br>64742-47-8      | 10 - 15                     | Petroleum distillates, hydrotreated light |
| 1,3,5-TRIMETHYLBENZENE<br>108-67-8 | 1 - 5                       | 1,3,5-Trimethylbenzene                    |
| XYLENE<br>1330-20-7                | 1 - 5                       | Xylenes (o-, m-, p- isomers)              |
| 1,2,4-TRIMETHYLBENZENE<br>95-63-6  | 1 - 5                       | 1,2,4-Trimethylbenzene                    |
| PROPRIETARY ADDITIVE               | 1 - 5                       | PROPRIETARY ADDITIVE                      |
| FOLPET<br>133-07-3                 | .1 - 1                      | Folpet                                    |
| ETHYLBENZENE<br>100-41-4           | .1 - 1                      | Ethyl benzene                             |

If this section is blank there are no hazardous components per OSHA guidelines.

### **4. FIRST AID MEASURES**

#### **Eye Contact:**

Get medical attention, if symptoms develop or persist. Immediately flush eye(s) with plenty of water. Remove any contact lenses and open eyes wide apart.

#### **Skin Contact:**

Remove contaminated clothing and shoes. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention, if symptoms develop or persist.

**Ingestion:**

Rinse mouth with water. Give one or two glasses of water. Only induce vomiting at the instruction of medical personnel. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head lower than hips to prevent aspiration. Get medical attention immediately.

**Inhalation:**

Move injured person into fresh air and keep person calm under observation. Get medical attention immediately. For breathing difficulties, oxygen may be necessary. If breathing stops, provide artificial respiration.

**Medical conditions aggravated by exposure:**

Any respiratory or skin condition.

## 5. FIRE FIGHTING MEASURES

|                                  |                                                                                                          |
|----------------------------------|----------------------------------------------------------------------------------------------------------|
| Flash point (Fahrenheit):        | 104                                                                                                      |
| Flash point (Celsius):           | 40                                                                                                       |
| Lower explosive limit (%):       | 1                                                                                                        |
| Upper explosive limit (%):       | 6                                                                                                        |
| Autoignition temperature:        | not determined                                                                                           |
| Sensitivity to impact:           | no                                                                                                       |
| Sensitivity to static discharge: | Can be sensitive to static discharge hazards. Please see bonding and grounding information in Section 7. |
| Hazardous combustion products:   | See Section 10.                                                                                          |

**Unusual fire and explosion hazards:**

Contaminated rags, wipes, saw dust, etc., may catch fire spontaneously. Store waste under water in closed metal containers or in approved self-closing containers designed to prevent spontaneous combustion until disposed of in compliance with applicable regulations. Oxidizing Material

**Extinguishing media:**

Carbon dioxide, dry chemical, foam and/or water fog.

**Fire fighting procedures:**

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

## 6. ACCIDENTAL RELEASE MEASURES

**Action to be taken if material is released or spilled:**

Ventilate the area. Avoid breathing dust or vapor. Use self-containing breathing apparatus or airmask for large spills in a confined area. Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 7, "Handling and Storage", for proper container and storage procedures. Remove all sources of ignition. Soak up with inert absorbent material. Use only non-sparking tools. Avoid contact with eyes.

## 7. HANDLING AND STORAGE

**Precautions to be taken in handling and storage:**

Keep away from heat, sparks and open flame. - No smoking. Keep container closed when not in use. Do not store above 120 degrees F. (49 degrees C). Based on flash point and vapor pressure, suitable storage should be provided in accordance with OSHA regulation 1910.106, Ontario OH&S regulation 851 section 22. Empty containers may contain product residue, including flammable or explosive vapors. Do not cut, puncture or weld on or near container. All label warnings must be observed until the container has been commercially cleaned or reconditioned. If the product is used near or above the flashpoint, an ignition hazard may be present. Activities, uses, or operations which liberate vapor (such as mixing or free fall of liquids) may also present an ignition hazard. Please ensure containers and other interconnected equipment are properly bonded and grounded at all times.

## 8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

## 8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

### Personal Protective Equipment

#### Eye and face protection:

Chemical goggles, also wear a face shield if splashing hazard exists.

#### Skin protection:

Appropriate chemical resistant gloves should be worn.

#### Other Personnel Protection Data:

To prevent skin contact wear protective clothing covering all exposed areas.

#### Respiratory protection:

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

#### Ventilation

Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas. Ovens used for curing should contain a fresh air purge to prevent vapours from accumulating and creating a possible explosive mixture. Where the product is used in a hazardous classified area, use explosion-proof electrical/ventilating/lighting/equipment.

### Exposure Guidelines

#### OSHA Permissible Exposure Limits (PEL's)

| Ingredient Name<br>CAS-No.    | Approx.<br>Weight % | TWA (final)                               | Ceilings limits (final) | Skin designations |
|-------------------------------|---------------------|-------------------------------------------|-------------------------|-------------------|
| STODDARD SOLVENT<br>8052-41-3 | 35 - 40             | 2900 mg/m <sup>3</sup> TWA<br>500 ppm TWA |                         |                   |
| XYLENE<br>1330-20-7           | 1 - 5               | 100 ppm TWA<br>435 mg/m <sup>3</sup> TWA  |                         |                   |
| ETHYLBENZENE<br>100-41-4      | .1 - 1              | 100 ppm TWA<br>435 mg/m <sup>3</sup> TWA  |                         |                   |

#### ACGIH Threshold Limit Value (TLV's)

| Ingredient Name<br>CAS-No.         | Approx.<br>Weight % | TWA                             | STEL         | Ceiling limits | Skin<br>designations |
|------------------------------------|---------------------|---------------------------------|--------------|----------------|----------------------|
| STODDARD SOLVENT<br>8052-41-3      | 35 - 40             | 100 ppm TWA                     |              |                |                      |
| 1,3,5-TRIMETHYLBENZENE<br>108-67-8 | 1 - 5               | 25 ppm                          |              |                |                      |
| XYLENE<br>1330-20-7                | 1 - 5               | 100 ppm TWA                     | 150 ppm STEL |                |                      |
| 1,2,4-TRIMETHYLBENZENE<br>95-63-6  | 1 - 5               | 25 PPM                          |              |                |                      |
| PROPRIETARY ADDITIVE               | 1 - 5               | 2 mg/m <sup>3</sup> TWA<br>fume |              |                |                      |
| ETHYLBENZENE<br>100-41-4           | .1 - 1              | 100 ppm TWA                     | 125 ppm STEL |                |                      |

## 9. PHYSICAL PROPERTIES

Odor:

Normal for this product type.

Physical State:

liquid

pH:

not determined

## 9. PHYSICAL PROPERTIES

|                                         |                               |
|-----------------------------------------|-------------------------------|
| Vapor pressure:                         | 90.2255639 mmHg @ 77°F (25°C) |
| Vapor density (air = 1.0):              | 5.1                           |
| Boiling point:                          | 219°F (104°C)                 |
| Solubility in water:                    | not determined                |
| Coefficient of water/oil distribution:  | not determined                |
| Density (lbs per US gallon):            | 7.32                          |
| Evaporation rate (butyl acetate = 1.0): | 1                             |
| Flash point (Fahrenheit):               | 104                           |
| Flash point (Celsius):                  | 40                            |
| Lower explosive limit (%):              | 1                             |
| Upper explosive limit (%):              | 6                             |
| Autoignition temperature:               | not determined                |

## 10. STABILITY AND REACTIVITY

|                                   |                                     |
|-----------------------------------|-------------------------------------|
| Stability:                        | Stable under normal conditions.     |
| Conditions to Avoid:              | Heat.                               |
| Incompatibility:                  | Strong oxidizing agents             |
| Hazardous Polymerization:         | None anticipated.                   |
| Hazardous Decomposition Products: | Carbon monoxide and carbon dioxide. |

**Sensitivity to static discharge:** Can be sensitive to static discharge hazards. Please see bonding and grounding information in Section 7.

## 11. TOXICOLOGICAL INFORMATION

| Ingredient Name<br>CAS-No.         | Approx.<br>Weight % | NIOSH - Selected LD50s and LC50s                                                                                                                  |
|------------------------------------|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| MINERAL SPIRITS<br>64742-47-8      | 10 - 15             | > 2000 mg/kg Dermal LD50 Rabbit<br>> 5.2 mg/L Inhalation LC50 Rat 4 h<br>> 5000 mg/kg Oral LD50 Rat                                               |
| 1,3,5-TRIMETHYLBENZENE<br>108-67-8 | 1 - 5               | = 24 g/m <sup>3</sup> Inhalation LC50 Rat 4 h<br>= 5000 mg/kg Oral LD50 Rat                                                                       |
| XYLENE<br>1330-20-7                | 1 - 5               | = 4300 mg/kg Oral LD50 Rat<br>= 47635 mg/L Inhalation LC50 Rat 4 h<br>= 5000 ppm Inhalation LC50 Rat 4 h<br>> 1700 mg/kg Dermal LD50 Rabbit       |
| 1,2,4-TRIMETHYLBENZENE<br>95-63-6  | 1 - 5               | = 18 g/m <sup>3</sup> Inhalation LC50 Rat 4 h<br>= 3400 mg/kg Oral LD50 Rat<br>> 3160 mg/kg Dermal LD50 Rabbit                                    |
| PROPRIETARY ADDITIVE               | 1 - 5               | > 3600 mg/kg Dermal LD50 Rabbit<br>> 3750 mg/kg Oral LD50 Rat                                                                                     |
| FOLPET<br>133-07-3                 | .1 - 1              | = 2636 mg/kg Oral LD50 Rat<br>> 0.48 g/m <sup>3</sup> Inhalation LC50 Rat 4 h<br>> 22600 mg/kg Dermal LD50 Rabbit<br>> 5000 mg/kg Dermal LD50 Rat |
| ETHYLBENZENE<br>100-41-4           | .1 - 1              | = 15354 mg/kg Dermal LD50 Rabbit<br>= 17.2 mg/L Inhalation LC50 Rat 4 h<br>= 3500 mg/kg Oral LD50 Rat                                             |

### Mutagens/Teratogens/Carcinogens:

Contains ethylbenzene, which has been determined by NTP to be an animal carcinogen with no known relevance to humans. IARC has classified ethylbenzene as possibly carcinogenic to humans (2b) on the basis of sufficient evidence of carcinogenicity in laboratory animals but inadequate evidence of cancer in humans.

| <b>Ingredient Name<br/>CAS-No.</b> | <b>Approx.<br/>Weight %</b> | <b>California Prop 65 - Reproductive<br/>(Female)</b> | <b>California Prop 65 - Carcinogen</b>       |
|------------------------------------|-----------------------------|-------------------------------------------------------|----------------------------------------------|
| FOLPET<br>133-07-3                 | .1 - 1                      |                                                       | Listed. initial date 1/1/89 - carcinogen     |
| ETHYLBENZENE<br>100-41-4           | .1 - 1                      |                                                       | Listed. initial date 6/11/04 -<br>carcinogen |

| <b>Ingredient Name<br/>CAS-No.</b> | <b>Approx.<br/>Weight %</b> | <b>IARC Group 1 - Human<br/>Evidence</b> | <b>IARC Group 2A - Limited<br/>Human Data</b> | <b>IARC Group 2B -<br/>Sufficient Animal Data</b> |
|------------------------------------|-----------------------------|------------------------------------------|-----------------------------------------------|---------------------------------------------------|
| ETHYLBENZENE<br>100-41-4           | .1 - 1                      |                                          |                                               | Monograph 77 [2000]                               |

| <b>Ingredient Name<br/>CAS-No.</b> | <b>Approx.<br/>Weight %</b> | <b>NTP Known<br/>Carcinogens</b> | <b>NTP Suspect<br/>Carcinogens</b> | <b>NTP Evidence of<br/>Carcinogenicity</b>                                                                         |
|------------------------------------|-----------------------------|----------------------------------|------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| XYLENE<br>1330-20-7                | 1 - 5                       |                                  |                                    | male rat-no evidence;<br>female rat-no evidence;<br>male mice-no evidence;<br>female mice-no evidence              |
| ETHYLBENZENE<br>100-41-4           | .1 - 1                      |                                  |                                    | male rat-clear evidence;<br>female rat-some<br>evidence; male mice-<br>some evidence; female<br>mice-some evidence |

| <b>Ingredient Name<br/>CAS-No.</b> | <b>Approx.<br/>Weight %</b> | <b>OSHA - Hazard<br/>Communication<br/>Carcinogens</b> | <b>OSHA - Specifically<br/>Regulated Carcinogens</b> | <b>ACGIH Carcinogens</b>                                                 |
|------------------------------------|-----------------------------|--------------------------------------------------------|------------------------------------------------------|--------------------------------------------------------------------------|
| ETHYLBENZENE<br>100-41-4           | .1 - 1                      | Present                                                |                                                      | A3 Confirmed Animal<br>Carcinogen with<br>Unknown Relevance to<br>Humans |

## 12. ECOLOGICAL DATA

No information on ecology is available.

## 13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

## 14. TRANSPORTATION INFORMATION

### U.S. Department of Transportation

UN ID Number (msds): UN1263  
 Proper Shipping Name: PAINT  
 Hazard Class: COMBUSTIBLE LIQUID  
 Packing Group: III

### U.S Hazmat and/or International DG shipment exceptions

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

### Reportable Quantity Description:

### International Air Transport Association (IATA):

UN ID Number (msds): UN1263  
 Proper Shipping Name: Paint  
 Hazard Class: 3  
 Packing Group: III

**International Maritime Organization (IMO):**

IMO UN/ID Number (msds): UN1263  
 Proper Shipping Name: PAINT  
 Hazard Class: 3  
 Packing Group: III  
 Marine Pollutant: YES  
 Marine Pollutant Ingredient 1: STODDARD SOLVENT  
 Marine Pollutant Ingredient 2: 1,3,5-TRIMETHYLBENZENE

**15. REGULATORY INFORMATION**

**U.S. FEDERAL REGULATIONS:**

| Ingredient Name<br>CAS-No.        | Approx.<br>Weight % | SARA 302 | SARA 313                                                          | CERCLA RQ in lbs. |
|-----------------------------------|---------------------|----------|-------------------------------------------------------------------|-------------------|
| XYLENE<br>1330-20-7               | 1 - 5               |          | form R reporting required<br>for 1.0% de minimis<br>concentration | 100               |
| 1,2,4-TRIMETHYLBENZENE<br>95-63-6 | 1 - 5               |          | Listed.                                                           |                   |
| FOLPET<br>133-07-3                | .1 - 1              |          | form R reporting required<br>for 1.0% de minimis<br>concentration |                   |
| ETHYLBENZENE<br>100-41-4          | .1 - 1              |          | form R reporting required<br>for 1.0% de minimis<br>concentration | 1000              |

**SARA 311/312 Hazard Class:**

Acute: yes  
 Chronic: yes  
 Flammability: yes  
 Reactivity: no  
 Sudden Pressure: no

**U.S. STATE REGULATIONS:**

**Right to Know:**

The specific chemical identity of a component may be withheld as a trade secret under 34 Pennsylvania Code, Chapter 317.

**Pennsylvania Right To Know:**

|                        |              |
|------------------------|--------------|
| 1,3,5-TRIMETHYLBENZENE | 108-67-8     |
| XYLENE                 | 1330-20-7    |
| MINERAL SPIRITS        | 64742-47-8   |
| PROPRIETARY ADDITIVE   | Trade Secret |
| STODDARD SOLVENT       | 8052-41-3    |
| 1,2,4-TRIMETHYLBENZENE | 95-63-6      |

**Additional Non-Hazardous Materials**

|                   |              |
|-------------------|--------------|
| PROPRIETARY RESIN | Trade Secret |
| PROPRIETARY OIL   | Trade Secret |

**California Proposition 65:**

WARNING: This product contains chemicals known to the State of California to cause cancer.

**Rule 66 status of product**

Photochemically reactive.

**INTERNATIONAL REGULATIONS - Chemical Inventories****US TSCA Inventory:**

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

**Canada Domestic Substances List:**

All components of this product are listed on the Domestic Substances List.

**16. OTHER INFORMATION****HMIS Codes**

|                      |                                                            |
|----------------------|------------------------------------------------------------|
| <b>Health:</b>       | 2*                                                         |
| <b>Flammability:</b> | 2                                                          |
| <b>Reactivity:</b>   | 1                                                          |
| <b>PPE:</b>          | X - See Section 8 for Personal Protective Equipment (PPE). |

**Abbreviations:**

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

**Disclaimer:**

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

**Preparation Information:**

|                |                               |
|----------------|-------------------------------|
| Prepared By:   | Regulatory Affairs Department |
| Print date:    | 12/Jul/2012                   |
| Revision Date: | 06/Dec/2011                   |