Miller/Ikett

REC'D MAY 14 2007

M A T E R I A L S A F E T Y D A T A S H E E T

XYLOL (XYLENE)

PRODUCT NAME: XYLOL (XYLENE)
PRODUCT CODE: 0000000000000006035

HMIS CODES: H F R P
2 3 0 G

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: REPCOLITE PAINTS, INC.
ADDRESS : 473 WEST 17th STREET
HOLLAND, MI 49423

EMERGENCY PHONE : 616-396-5213
INFORMATION PHONE : 616-396-5213 NAME OF PREPARER : DA

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP		WEIGHT PERCENT
* Mixed Xylenes, Ethylbenzene OSHA PEL: 100 ppm, ACGIH TLV: 300 ppm	1330-20-7	9.5	68 degF	100

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 280 deg F
SPECIFIC GRAVITY (H2O=1): 0.87
VAPOR DENSITY: HEAVIER THAN AIR
EVAPORATION RATE: SLOWER THAN ETHER
COATING V.O.C.: 7.23 lb/gl
SOLUBILITY IN WATER: NON-SOLUABLE
APPEARANCE AND ODOR: LIQUID, STRONG SOLVENT ODOR

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 81 deg F
METHOD USED: TCC
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1 UPPER: 7

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES
Water should be used to cool containers to prevent pressure build up which could result in container rupture.

UNUSUAL FIRE AND EXPLOSION HAZARDS
Vapor accumulations and spray mist may flash or explode if ignited. Water should be used to cool containers to prevent pressure build up which could result in container rupture. Vapors are heavier than air and may travel along the ground to ignition sources at locations distant from material handling point.

SECTION V - REACTIVITY DATA

STABILITY: STABLE
CONDITIONS TO AVOID: N/A

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS
May produce fumes when heated to decomposition. Fumes may contain carbon monoxide and carbon dioxide.

002 REPCOLITE PAINTS 05/04/2007 14:03 FAX 6163989654