SAFETY DATA SHEET

NAME OF PRODUCT: SLIPIT® Sliding Compound

SDS DATE: AUGUST 2015

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SLIPIT® Sliding Compound

SYNONYMS:

PRODUCT CODES: 10435, 40435, 16435, 32435, 50435, xx435

MANUFACTURER: SLIPIT industries, Inc.

ADDRESS: PO Box 205

Tillson, NY 12486-0205

EMERGENCY PHONE: 800-255-3924 CHEM-TELL PHONE: 800-255-3924 OTHER CALLS: 845-778-7219 FAX PHONE: 845-778-2265

CHEMICAL FAMILY: Petroleum hydrocarbons

PRODUCT USE: Lubricant

SECTION 2: HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYES: Yes - Irritation
SKIN: Yes-Slight Irritation

INGESTION: Yes INHALATION: Yes

ACUTE HEALTH HAZARDS: None Known
CHRONIC HEALTH HAZARDS: None Known

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None known

CARCINOGENICITY

OSHA: No ACGIH: NTP: No IARC: No

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Product name: SLIPIT® Sliding Compound

Hazaradous Ingredients: No hazardous ingredients

Composition: The specific composition is proprietary and withheld.

SECTION 3 NOTES:

Letter of Guarantee for entrance into USDA inspected sites may be found at www.slipit.com. FDA accepted for use in applications with incidental food contact in accordance with CFR 178.3570. CFIA accepted for use in applications with incidental food contact.

SECTION 4: FIRST AID MEASURES

EYES: Flush with plenty of water SKIN: Wash with soap and water

INGESTION: Non-toxic – Induction of vomiting not required

INHALATION: Remove to fresh air.

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR, UPPER: Not determined (% BY VOLUME) LOWER: Not determined

FLASH POINT: 395 F (COC)

AUTOIGNITION TEMPERATURE: 675 F (Estimated)

NFPA HAZARD CLASSIFICATION

HEALTH: 0 FLAMMABILITY: 1 REACTIVITY: 0

HMIS HAZARD CLASSIFICATION

HEALTH: 0 FLAMMABILITY: 1 REACTIVITY: 0

EXTINGUISHING MEDIA: Dry chemical powder, CO-2, Foam

SPECIAL FIRE FIGHTING PROCEDURES: Fire fighters should wear a NIOSH approved, pressure demand, self-contained breathing

apparatus when fighting fires.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Monoxide, Carbon Dioxide

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: Contain spill – absorb with inert material. Do not use combustible materials such as sawdust.

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE: Do not transfer to unmarked containers. Store away from excessive heat, sparks, open flame or oxidizing materials. This product is not classified under DOT Regulations. NFPA Class 111B Storage.

OTHER PRECAUTIONS: No additional precautions or labels.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS:

VENTILATION: Local Exhaust: If needed to maintain workable concentration elow permissible exposure limit.

RESPIRATORY PROTECTION:

EYE PROTECTION:

Not required under conditions of normal use.

Not required under conditions of normal use of normal use.

Not required under conditions of normal use.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None WORK HYGIENIC PRACTICES: No unusual precautions

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Cream color
ODOR: Little or no odor
PHYSICAL STATE: Soft Paste
pH AS SUPPLIED: NA

BOILING RANGE: 570 F – 900 F Wide Range

MELTING POINT: 130 F

FREEZING POINT: ND

VAPOR PRESSURE (mmHg): below .0001 @ 20 C

VAPOR DENSITY (AIR = 1): N/A

SPECIFIC GRAVITY (H2O = 1): 0.945 @ 20 C

EVAPORATION RATE: Nil SOLUBILITY IN WATER: Nil

PERCENT SOLIDS BY WEIGHT: 100%

PERCENT VOLATILE: 0%

VOLATILE ORGANIC COMPOUNDS (VOC): 0%

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID (STABILITY): Sparks – Open Flame

INCOMPATIBILITY (MATERIAL TO AVOID): Strong oxidizers like chlorine and concentrated oxygen.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Incomplete combustion will produce carbon monoxide and carbon dioxide.

HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS TO AVOID (POLYMERIZATION): NA

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: LD50 (g/kg) - Les than 30

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No Data Available

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: In accordance with federal, state and local regulations. Do not flush to drain/storm sewer. Contract

authorized disposal service.

RCRA HAZARD CLASS: Non-Hazardous Waste

SECTION 14: TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION

PROPER SHIPPING NAME: Petroleum Lubricant Paste

HAZARD CLASS: NA (Non-Hazardous)

ID NUMBER: NA

PACKING GROUP: NA

LABEL STATEMENT: NA - None Required

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA (TOXIC SUBSTANCE CONTROL ACT): All Components Listed

311/312 HAZARD CATEGORIES: Acute: No Chronic: No Fire: No Reactivity: No

SECTION 16: OTHER INFORMATION

OTHER INFORMATION: None