

# SAFETY DATA SHEET

## 1. Identification

**Product identifier** Safe Slip Yellow

**Other means of identification**

**Product code** 1116Y

**Recommended use** Slip resistant epoxy coating

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufacturer**

**Company Name** AIS Specialty Products, Inc

**Address** 9831 Independence Ave.

**City** Chatsworth

**State** CA

**Zip** 91311

**Country** United States

**Telephone** 1 (818) 626-9870

**Contact person** Brian Stark

**Website** [www.specialtyproductsusa.com](http://www.specialtyproductsusa.com)

**E-mail** [Brian@specialtyproductsusa.com](mailto:Brian@specialtyproductsusa.com)

**Emergency phone number** 1 (800) 424-9300 (CHEMTREC - Contract # 8730) USA & Canada  
+1 703-527-3887 (CHEMTREC - Contract # 8730) Outside USA and Canada

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols Category 1

**Health hazards** Acute toxicity, oral Category 4

Acute toxicity, dermal Category 4

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A

Carcinogenicity Category 2

Reproductive toxicity (the unborn child) Category 2

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated exposure Category 1

**Environmental hazards** Hazardous to the aquatic environment, acute hazard Category 3

Hazardous to the aquatic environment, long-term hazard Category 3

**OSHA defined hazards** Not classified.

**Label elements**



**Signal word** Danger

**Hazard statement** Extremely flammable aerosol. Harmful if swallowed. Harmful in contact with skin. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging the unborn child. Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

## Precautionary statement

### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

### Response

If swallowed: Call a poison center/doctor if you feel unwell. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Rinse mouth. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

### Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

### Hazard(s) not otherwise classified (HNOC)

None known.

### Supplemental information

75.83% of the mixture consists of component(s) of unknown acute oral toxicity. 89.6% of the mixture consists of component(s) of unknown acute dermal toxicity. 73.62% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 73.62% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

## 3. Composition/information on ingredients

### Mixtures

| Chemical name    | Common name and synonyms | CAS number | %     |
|------------------|--------------------------|------------|-------|
| ACETONE          |                          | 67-64-1    | 20-35 |
| BUTANE           |                          | 106-97-8   | 10-25 |
| PROPANE          |                          | 74-98-6    | 10-25 |
| TOLUENE          |                          | 108-88-3   | 10-25 |
| XYLENE           |                          | 1330-20-7  | 10-25 |
| CLAY             |                          | 1332-58-7  | <10   |
| ETHYL BENZENE    |                          | 100-41-4   | <10   |
| TITANIUM DIOXIDE |                          | 13463-67-7 | <10   |

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

### Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

### Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

### Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

### Ingestion

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.

### Most important symptoms/effects, acute and delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

### Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

### General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

## 5. Fire-fighting measures

|                                                                      |                                                                                                                                                                                                                                                                            |
|----------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Suitable extinguishing media</b>                                  | Powder. Alcohol resistant foam. Carbon dioxide (CO <sub>2</sub> ).                                                                                                                                                                                                         |
| <b>Unsuitable extinguishing media</b>                                | Do not use water jet as an extinguisher, as this will spread the fire.                                                                                                                                                                                                     |
| <b>Specific hazards arising from the chemical</b>                    | Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.                                                                                                                            |
| <b>Special protective equipment and precautions for firefighters</b> | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.                                                                                                           |
| <b>Fire fighting equipment/instructions</b>                          | Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. |
| <b>Specific methods</b>                                              | Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.                                                       |
| <b>General fire hazards</b>                                          | Extremely flammable aerosol.                                                                                                                                                                                                                                               |

## 6. Accidental release measures

|                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|----------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Personal precautions, protective equipment and emergency procedures</b> | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| <b>Methods and materials for containment and cleaning up</b>               | Refer to attached safety data sheets and/or instructions for use. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Following product recovery, flush area with water.       |
| <b>Environmental precautions</b>                                           | Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.<br>Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.                                             |

## 7. Handling and storage

|                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Precautions for safe handling</b>                                | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices. |
| <b>Conditions for safe storage, including any incompatibilities</b> | Level 3 Aerosol.<br>Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components            | Type | Value                              | Form                 |
|-----------------------|------|------------------------------------|----------------------|
| ACETONE (CAS 67-64-1) | PEL  | 2400 mg/m <sup>3</sup><br>1000 ppm |                      |
| CLAY (CAS 1332-58-7)  | PEL  | 5 mg/m <sup>3</sup>                | Respirable fraction. |

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

| Components                        | Type | Value                 | Form        |
|-----------------------------------|------|-----------------------|-------------|
| ETHYL BENZENE (CAS 100-41-4)      | PEL  | 15 mg/m3<br>435 mg/m3 | Total dust. |
| PROPANE (CAS 74-98-6)             | PEL  | 100 ppm<br>1800 mg/m3 |             |
| TITANIUM DIOXIDE (CAS 13463-67-7) | PEL  | 1000 ppm<br>15 mg/m3  | Total dust. |
| XYLENE (CAS 1330-20-7)            | PEL  | 435 mg/m3<br>100 ppm  |             |

**US. OSHA Table Z-2 (29 CFR 1910.1000)**

| Components             | Type           | Value              |
|------------------------|----------------|--------------------|
| TOLUENE (CAS 108-88-3) | Ceiling<br>TWA | 300 ppm<br>200 ppm |

**US. ACGIH Threshold Limit Values**

| Components                        | Type        | Value              | Form                 |
|-----------------------------------|-------------|--------------------|----------------------|
| ACETONE (CAS 67-64-1)             | STEL<br>TWA | 750 ppm<br>500 ppm |                      |
| BUTANE (CAS 106-97-8)             | STEL        | 1000 ppm           |                      |
| CLAY (CAS 1332-58-7)              | TWA         | 2 mg/m3            | Respirable fraction. |
| ETHYL BENZENE (CAS 100-41-4)      | TWA         | 20 ppm             |                      |
| TITANIUM DIOXIDE (CAS 13463-67-7) | TWA         | 10 mg/m3           |                      |
| TOLUENE (CAS 108-88-3)            | TWA         | 20 ppm             |                      |
| XYLENE (CAS 1330-20-7)            | STEL<br>TWA | 150 ppm<br>100 ppm |                      |

**Biological limit values**
**ACGIH Biological Exposure Indices**

| Components                   | Value     | Determinant                                   | Specimen            | Sampling Time |
|------------------------------|-----------|-----------------------------------------------|---------------------|---------------|
| ACETONE (CAS 67-64-1)        | 50 mg/l   | Acetone                                       | Urine               | *             |
| ETHYL BENZENE (CAS 100-41-4) | 0.15 g/g  | Sum of mandelic acid and phenylglyoxylic acid | Creatinine in urine | *             |
| TOLUENE (CAS 108-88-3)       | 0.3 mg/g  | o-Cresol, with hydrolysis                     | Creatinine in urine | *             |
|                              | 0.03 mg/l | Toluene                                       | Urine               | *             |
|                              | 0.02 mg/l | Toluene                                       | Blood               | *             |
| XYLENE (CAS 1330-20-7)       | 1.5 g/g   | Methylhippuric acids                          | Creatinine in urine | *             |

\* - For sampling details, please see the source document.

**Exposure guidelines**
**US - California OELs: Skin designation**

TOLUENE (CAS 108-88-3) Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies**

TOLUENE (CAS 108-88-3) Skin designation applies.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

**Individual protection measures, such as personal protective equipment**

|                                       |                                                                                                                                                                                                                                                                               |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Eye/face protection</b>            | Chemical respirator with organic vapor cartridge and full facepiece.                                                                                                                                                                                                          |
| <b>Skin protection</b>                |                                                                                                                                                                                                                                                                               |
| <b>Hand protection</b>                | Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.                                                                                                                                                                         |
| <b>Other</b>                          | Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.                                                                                                                                                                                      |
| <b>Respiratory protection</b>         | Chemical respirator with organic vapor cartridge and full facepiece.                                                                                                                                                                                                          |
| <b>Thermal hazards</b>                | Wear appropriate thermal protective clothing, when necessary.                                                                                                                                                                                                                 |
| <b>General hygiene considerations</b> | When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. |

**9. Physical and chemical properties**

|                                                     |                                           |
|-----------------------------------------------------|-------------------------------------------|
| <b>Appearance</b>                                   | Aerosol.                                  |
| <b>Physical state</b>                               | Liquid.                                   |
| <b>Form</b>                                         | Aerosol.                                  |
| <b>Color</b>                                        | Yellow                                    |
| <b>Odor</b>                                         | Epoxy.                                    |
| <b>Odor threshold</b>                               | Not available.                            |
| <b>pH</b>                                           | Not available.                            |
| <b>Melting point/freezing point</b>                 | Not available.                            |
| <b>Initial boiling point and boiling range</b>      | 98.22 °F (36.79 °C) estimated             |
| <b>Flash point</b>                                  | -133.6 °F (-92.0 °C)                      |
| <b>Evaporation rate</b>                             | Not available.                            |
| <b>Flammability (solid, gas)</b>                    | Not applicable.                           |
| <b>Upper/lower flammability or explosive limits</b> |                                           |
| <b>Flammability limit - lower (%)</b>               | 2.2 % estimated                           |
| <b>Flammability limit - upper (%)</b>               | 10.2 % estimated                          |
| <b>Explosive limit - lower (%)</b>                  | Not available.                            |
| <b>Explosive limit - upper (%)</b>                  | Not available.                            |
| <b>Vapor pressure</b>                               | 2262.95 hPa estimated                     |
| <b>Vapor density</b>                                | Not available.                            |
| <b>Relative density</b>                             | Not available.                            |
| <b>Solubility(ies)</b>                              |                                           |
| <b>Solubility (water)</b>                           | 0 %                                       |
| <b>Partition coefficient (n-octanol/water)</b>      | Not available.                            |
| <b>Auto-ignition temperature</b>                    | 550 °F (287.78 °C) estimated              |
| <b>Decomposition temperature</b>                    | Not available.                            |
| <b>Viscosity</b>                                    | Not available.                            |
| <b>Other information</b>                            |                                           |
| <b>Density</b>                                      | 6.50 lb/gal                               |
| <b>Flammability class</b>                           | Flammable IA estimated                    |
| <b>Percent volatile</b>                             | 78.66 %w/w                                |
| <b>Specific gravity</b>                             | 0.78                                      |
| <b>VOC (Weight %)</b>                               | 402.67 g/l MATERIAL<br>548.66 g/l COATING |

## 10. Stability and reactivity

|                                           |                                                                                               |
|-------------------------------------------|-----------------------------------------------------------------------------------------------|
| <b>Reactivity</b>                         | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| <b>Chemical stability</b>                 | Material is stable under normal conditions.                                                   |
| <b>Possibility of hazardous reactions</b> | Hazardous polymerization does not occur.                                                      |
| <b>Conditions to avoid</b>                | Avoid temperatures exceeding the flash point. Contact with incompatible materials.            |
| <b>Incompatible materials</b>             | Strong acids. Acids. Strong oxidizing agents. Nitrates. Halogens. Fluorine. Chlorine.         |
| <b>Hazardous decomposition products</b>   | No hazardous decomposition products are known.                                                |

## 11. Toxicological information

### Information on likely routes of exposure

|                     |                                                                                                                                                                                       |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Inhalation</b>   | May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful. |
| <b>Skin contact</b> | Harmful in contact with skin. Causes skin irritation.                                                                                                                                 |
| <b>Eye contact</b>  | Causes serious eye irritation.                                                                                                                                                        |
| <b>Ingestion</b>    | Harmful if swallowed.                                                                                                                                                                 |

|                                                                                     |                                                                                                                                                                                                                    |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Symptoms related to the physical, chemical and toxicological characteristics</b> | Headache. May cause drowsiness and dizziness. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### Information on toxicological effects

|                                          |                                                                       |
|------------------------------------------|-----------------------------------------------------------------------|
| <b>Acute toxicity</b>                    | Harmful in contact with skin. Harmful if swallowed. Narcotic effects. |
| <b>Skin corrosion/irritation</b>         | Causes skin irritation.                                               |
| <b>Serious eye damage/eye irritation</b> | Causes serious eye irritation.                                        |

### Respiratory or skin sensitization

|                                  |                                                           |
|----------------------------------|-----------------------------------------------------------|
| <b>Respiratory sensitization</b> | Not a respiratory sensitizer.                             |
| <b>Skin sensitization</b>        | This product is not expected to cause skin sensitization. |

|                               |                                                                                                                  |
|-------------------------------|------------------------------------------------------------------------------------------------------------------|
| <b>Germ cell mutagenicity</b> | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |
|-------------------------------|------------------------------------------------------------------------------------------------------------------|

|                        |                              |
|------------------------|------------------------------|
| <b>Carcinogenicity</b> | Suspected of causing cancer. |
|------------------------|------------------------------|

### IARC Monographs. Overall Evaluation of Carcinogenicity

|                                   |                                                     |
|-----------------------------------|-----------------------------------------------------|
| ETHYL BENZENE (CAS 100-41-4)      | 2B Possibly carcinogenic to humans.                 |
| TITANIUM DIOXIDE (CAS 13463-67-7) | 2B Possibly carcinogenic to humans.                 |
| TOLUENE (CAS 108-88-3)            | 3 Not classifiable as to carcinogenicity to humans. |
| XYLENE (CAS 1330-20-7)            | 3 Not classifiable as to carcinogenicity to humans. |

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

### US. National Toxicology Program (NTP) Report on Carcinogens

Not available.

|                                                           |                                                                                                                                                             |
|-----------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Reproductive toxicity</b>                              | Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child. |
| <b>Specific target organ toxicity - single exposure</b>   | May cause drowsiness and dizziness.                                                                                                                         |
| <b>Specific target organ toxicity - repeated exposure</b> | Causes damage to organs through prolonged or repeated exposure.                                                                                             |
| <b>Aspiration hazard</b>                                  | Not an aspiration hazard.                                                                                                                                   |
| <b>Chronic effects</b>                                    | Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.          |

## 12. Ecological information

|                    |                                                    |
|--------------------|----------------------------------------------------|
| <b>Ecotoxicity</b> | Harmful to aquatic life with long lasting effects. |
|--------------------|----------------------------------------------------|

| Components                        |      | Species                                             | Test Results                   |
|-----------------------------------|------|-----------------------------------------------------|--------------------------------|
| ACETONE (CAS 67-64-1)             |      |                                                     |                                |
| Aquatic                           |      |                                                     |                                |
| Crustacea                         | EC50 | Water flea (Daphnia magna)                          | 10294 - 17704 mg/l, 48 hours   |
| Fish                              | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 4740 - 6330 mg/l, 96 hours     |
| ETHYL BENZENE (CAS 100-41-4)      |      |                                                     |                                |
| Aquatic                           |      |                                                     |                                |
| Crustacea                         | EC50 | Water flea (Daphnia magna)                          | 1.37 - 4.4 mg/l, 48 hours      |
| Fish                              | LC50 | Bluegill (Lepomis macrochirus)                      | 7.711 - 9.591 mg/l, 96 hours   |
|                                   |      | Fathead minnow (Pimephales promelas)                | 11.5 - 12.7 mg/l, 96 hours     |
| TITANIUM DIOXIDE (CAS 13463-67-7) |      |                                                     |                                |
| Aquatic                           |      |                                                     |                                |
| Crustacea                         | EC50 | Water flea (Daphnia magna)                          | > 1000 mg/l, 48 hours          |
| Fish                              | LC50 | Mummichog (Fundulus heteroclitus)                   | > 1000 mg/l, 96 hours          |
| TOLUENE (CAS 108-88-3)            |      |                                                     |                                |
| Aquatic                           |      |                                                     |                                |
| Crustacea                         | EC50 | Water flea (Daphnia magna)                          | 19.6 mg/l, 48 hours            |
| Fish                              | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 14.1 - 17.16 mg/l, 96 hours    |
| XYLENE (CAS 1330-20-7)            |      |                                                     |                                |
| Aquatic                           |      |                                                     |                                |
| Fish                              | LC50 | Bluegill (Lepomis macrochirus)                      | 10.464 - 16.114 mg/l, 96 hours |
|                                   |      |                                                     | 7.711 - 9.591 mg/l, 96 hours   |

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

#### Bioaccumulative potential

##### Partition coefficient n-octanol / water (log Kow)

|               |            |
|---------------|------------|
| ACETONE       | -0.24      |
| BUTANE        | 2.89       |
| ETHYL BENZENE | 3.15       |
| PROPANE       | 2.36       |
| TOLUENE       | 2.73       |
| XYLENE        | 3.12 - 3.2 |

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

|                                              |                                                                                                                                                                                                                                                                                                                                                                                                         |
|----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Disposal instructions</b>                 | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations. |
| <b>Local disposal regulations</b>            | Dispose in accordance with all applicable regulations.                                                                                                                                                                                                                                                                                                                                                  |
| <b>Hazardous waste code</b>                  | The waste code should be assigned in discussion between the user, the producer and the waste disposal company.                                                                                                                                                                                                                                                                                          |
| <b>Waste from residues / unused products</b> | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).                                                                                                                                                                                        |
| <b>Contaminated packaging</b>                | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.                                                                                                                                                              |

## 14. Transport information

### DOT

|                              |                                                                         |
|------------------------------|-------------------------------------------------------------------------|
| UN number                    | UN1950                                                                  |
| UN proper shipping name      | Aerosols, flammable                                                     |
| Transport hazard class(es)   |                                                                         |
| Class                        | 2.1                                                                     |
| Subsidiary risk              | -                                                                       |
| Label(s)                     | 2.1                                                                     |
| Packing group                | Not applicable.                                                         |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Special provisions           | Limited Quantity                                                        |
| Packaging exceptions         | 306                                                                     |
| Packaging non bulk           | None                                                                    |
| Packaging bulk               | None                                                                    |

### IATA

|                              |                                                                         |
|------------------------------|-------------------------------------------------------------------------|
| UN number                    | ID8000                                                                  |
| UN proper shipping name      | Consumer commodity                                                      |
| Transport hazard class(es)   |                                                                         |
| Class                        | 9                                                                       |
| Subsidiary risk              | ORM-D                                                                   |
| Packing group                | Not applicable.                                                         |
| Environmental hazards        | No.                                                                     |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Other information            |                                                                         |
| Passenger and cargo aircraft | Allowed.                                                                |
| Cargo aircraft only          | Allowed.                                                                |

### IMDG

|                              |                                                                         |
|------------------------------|-------------------------------------------------------------------------|
| UN number                    | UN1950                                                                  |
| UN proper shipping name      | Aerosols, flammable                                                     |
| Transport hazard class(es)   |                                                                         |
| Class                        | 2.1                                                                     |
| Subsidiary risk              | -                                                                       |
| Label(s)                     | 2.1                                                                     |
| Packing group                | Not applicable.                                                         |
| Environmental hazards        |                                                                         |
| Marine pollutant             | No.                                                                     |
| EmS                          | F-D, S-U                                                                |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

### DOT





## 15. Regulatory information

### US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

One or more components are not listed on TSCA.

### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

### CERCLA Hazardous Substance List (40 CFR 302.4)

|                              |         |
|------------------------------|---------|
| ACETONE (CAS 67-64-1)        | Listed. |
| BUTANE (CAS 106-97-8)        | Listed. |
| ETHYL BENZENE (CAS 100-41-4) | Listed. |
| PROPANE (CAS 74-98-6)        | Listed. |
| TOLUENE (CAS 108-88-3)       | Listed. |
| XYLENE (CAS 1330-20-7)       | Listed. |

### SARA 304 Emergency release notification

Not regulated.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Hazard categories

Immediate Hazard - Yes  
Delayed Hazard - Yes  
Fire Hazard - Yes  
Pressure Hazard - No  
Reactivity Hazard - No

### SARA 302 Extremely hazardous substance

Not listed.

**SARA 311/312 Hazardous chemical** No

### SARA 313 (TRI reporting)

| Chemical name | CAS number | % by wt. |
|---------------|------------|----------|
| TOLUENE       | 108-88-3   | 10-25    |
| XYLENE        | 1330-20-7  | 10-25    |
| ETHYL BENZENE | 100-41-4   | <10      |

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

ETHYL BENZENE (CAS 100-41-4)  
TOLUENE (CAS 108-88-3)  
XYLENE (CAS 1330-20-7)

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

BUTANE (CAS 106-97-8)  
PROPANE (CAS 74-98-6)

**Safe Drinking Water Act (SDWA)** Not regulated.

#### Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

ACETONE (CAS 67-64-1) 6532  
TOLUENE (CAS 108-88-3) 6594

#### Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

ACETONE (CAS 67-64-1) 35 %WV

|                                                 |        |
|-------------------------------------------------|--------|
| TOLUENE (CAS 108-88-3)                          | 35 %WV |
| <b>DEA Exempt Chemical Mixtures Code Number</b> |        |
| ACETONE (CAS 67-64-1)                           | 6532   |
| TOLUENE (CAS 108-88-3)                          | 594    |

## US state regulations

### US - California Candidate Chemicals: Listed

ACETONE (CAS 67-64-1)  
 BUTANE (CAS 106-97-8)  
 TITANIUM DIOXIDE (CAS 13463-67-7)

### US - California Candidate Chemicals: Listed on initial list

ETHYL BENZENE (CAS 100-41-4)  
 TOLUENE (CAS 108-88-3)  
 XYLENE (CAS 1330-20-7)

### US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

### US. Massachusetts RTK - Substance List

ACETONE (CAS 67-64-1)  
 BUTANE (CAS 106-97-8)  
 CLAY (CAS 1332-58-7)  
 ETHYL BENZENE (CAS 100-41-4)  
 PROPANE (CAS 74-98-6)  
 TITANIUM DIOXIDE (CAS 13463-67-7)  
 TOLUENE (CAS 108-88-3)  
 XYLENE (CAS 1330-20-7)

### US. New Jersey Worker and Community Right-to-Know Act

ACETONE (CAS 67-64-1)  
 BUTANE (CAS 106-97-8)  
 CLAY (CAS 1332-58-7)  
 ETHYL BENZENE (CAS 100-41-4)  
 PROPANE (CAS 74-98-6)  
 TITANIUM DIOXIDE (CAS 13463-67-7)  
 TOLUENE (CAS 108-88-3)  
 XYLENE (CAS 1330-20-7)

### US. Pennsylvania Worker and Community Right-to-Know Law

ACETONE (CAS 67-64-1)  
 BUTANE (CAS 106-97-8)  
 CLAY (CAS 1332-58-7)  
 ETHYL BENZENE (CAS 100-41-4)  
 PROPANE (CAS 74-98-6)  
 TITANIUM DIOXIDE (CAS 13463-67-7)  
 TOLUENE (CAS 108-88-3)  
 XYLENE (CAS 1330-20-7)

### US. Rhode Island RTK

ACETONE (CAS 67-64-1)  
 BUTANE (CAS 106-97-8)  
 ETHYL BENZENE (CAS 100-41-4)  
 PROPANE (CAS 74-98-6)  
 TOLUENE (CAS 108-88-3)  
 XYLENE (CAS 1330-20-7)

### US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

#### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

|                                            |                           |
|--------------------------------------------|---------------------------|
| CRYSTALLINE QUARTZ SILICA (CAS 14808-60-7) | Listed: October 1, 1988   |
| ETHYL BENZENE (CAS 100-41-4)               | Listed: June 11, 2004     |
| TITANIUM DIOXIDE (CAS 13463-67-7)          | Listed: September 2, 2011 |

#### US - California Proposition 65 - CRT: Listed date/Developmental toxin

|                        |                         |
|------------------------|-------------------------|
| TOLUENE (CAS 108-88-3) | Listed: January 1, 1991 |
|------------------------|-------------------------|

#### US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

|                        |                        |
|------------------------|------------------------|
| TOLUENE (CAS 108-88-3) | Listed: August 7, 2009 |
|------------------------|------------------------|

## International Inventories

| Country(s) or region        | Inventory name                                                         | On inventory (yes/no)* |
|-----------------------------|------------------------------------------------------------------------|------------------------|
| Australia                   | Australian Inventory of Chemical Substances (AICS)                     | No                     |
| Canada                      | Domestic Substances List (DSL)                                         | No                     |
| Canada                      | Non-Domestic Substances List (NDSL)                                    | No                     |
| China                       | Inventory of Existing Chemical Substances in China (IECSC)             | No                     |
| Europe                      | European Inventory of Existing Commercial Chemical Substances (EINECS) | No                     |
| Europe                      | European List of Notified Chemical Substances (ELINCS)                 | No                     |
| Japan                       | Inventory of Existing and New Chemical Substances (ENCS)               | No                     |
| Korea                       | Existing Chemicals List (ECL)                                          | No                     |
| New Zealand                 | New Zealand Inventory                                                  | No                     |
| Philippines                 | Philippine Inventory of Chemicals and Chemical Substances (PICCS)      | No                     |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory                          | No                     |

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

|               |                                                     |
|---------------|-----------------------------------------------------|
| Issue date    | 12-20-2015                                          |
| Version #     | 01                                                  |
| HMIS® ratings | Health: 2*<br>Flammability: 4<br>Physical hazard: 0 |
| NFPA ratings  | Health: 2<br>Flammability: 4<br>Instability: 0      |
| NFPA ratings  |                                                     |



### Disclaimer

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create any warranty, expressed or implied. It is the responsibility of the user to determine the applicability of this information and the suitability of the material or product for any particular purpose.