

DICK BLICK -- MATTE FIXATIVE;8044-00 -- 8030-00N000401

=====  
Product Identification  
=====

Product ID:MATTE FIXATIVE;8044-00  
MSDS Date:01/01/1985  
FSC:8030  
NIIN:00N000401  
MSDS Number: BCFJR  
=== Responsible Party ===  
Company Name:DICK BLICK  
Address:P O BOX 1267  
City:GALESBURG  
State:IL  
ZIP:61401  
Country:US  
CAGE:GO856

==== Contractor Identification ===

Company Name:BLICK DICK CO  
Address:P O BOX 1267  
Box:City:GALESBURG  
State:IL  
ZIP:61401  
Country:US  
Phone:309-343-6181  
CAGE:06608  
Company Name:DICK BLICK  
Address:P O BOX 1267  
Box:City:GALESBURG  
State:IL  
ZIP:61401  
Country:US  
CAGE:GO856

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 35.0%  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:METHYLENE CHLORIDE (SARA III)  
CAS:75-09-2  
RTECS #:PA8050000  
Fraction by Wt: 33.0%  
OSHA PEL:500 PPM/C,1000; Z2  
ACGIH TLV:50 PPM, A2; 9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA III)  
CAS:67-64-1  
RTECS #:AL3150000

Fraction by Wt: 32.0%  
OSHA PEL:1000PPM  
ACGIH TLV:750PPM/1000STEL;9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

=====  
Hazards Identification  
=====

Effects of Overexposure:MODERATELY TOXIC FROM INH, SKIN  
CNTCT/ABSORPTION, EYE CNTCT, INGEST. CNS DEPRSS, ANEMIA, LEUKNPN.

=====  
First Aid Measures  
=====

First Aid:EYES: FLUSH W/EYE WASH OR WATER FOR 15 MIN. SKIN: WIPE OFF,  
WASH CNTCTD AREA. INH: REMOVE TO FRESH AIR. INGEST: DO NOT INDUCE  
VOMIT, GET MD PROMPTLY.

=====  
Fire Fighting Measures  
=====

Flash Point:3F TCC  
Lower Limits:2.6  
Upper Limits:12.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:ADD SOLID ABSORBENT, SCOOP INTO DISPOSAL CART,  
HOSE OR WASH DOWN AREA.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:AVOID OPEN FLAME OR FIRE, STORE IN  
COOL, VENT AREA.  
Other Precautions:GROUND EQUIP TO REDUCE ELECTRICAL SPARKING.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:NIOSH/MSHA APPRVD SELF-CNTND EQUIP IF VAPOR  
EXCEEDS TLV.  
Ventilation:MFR REC LOCAL EXH  
Eye Protection:SAFETY GLASSES/GOGGLES  
Supplemental Safety and Health  
AUTOIGNITION TEMP: 1000 F.

=====  
Physical/Chemical Properties  
=====

Boiling Pt:B.P. Text:55C  
Vapor Density:2.73  
Spec Gravity:1.0400  
Appearance and Odor:MILD AROMATIC ODOR; WATER WHITE LIQUID  
Percent Volatiles by Volume:100

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES  
WILL REACT W/STRONG OXIDIZING MATLS  
Hazardous Decomposition Products:CO, CO\*2

===== Disposal Considerations =====

Waste Disposal Methods: BURY DRUMS IN APPRVD DUMP OR INCINRATE IF IAW  
FED, STATE, LOCAL REG.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.